



<b>Project:</b>	
<b>Location:</b>	
<b>Model#:</b> TLCN-CWRGBW30-BK	<b>Type:</b>
<b>Client:</b>	<b>Qty:</b>
<b>Prepared by:</b>	<b>Date:</b>

SERIES SPECIFICATIONS

To supply and install TamLite's TLCN Series of RF Remote Controller as specified. The 6 pre-set 6 Zone Dimming RF Remote Control shall operate at 4.5VDC. To be used to control low voltage luminaires when paired with an appropriate TamLite RF receiver. Communication Frequency - 916.66 MHz (Transmission distance 30 Meters Max)

PERFORMANCE SPECIFICATIONS

**Environmental Rating(s):** IP20                      **UL Classification:** Dry Location Only                      **Ambient Operating Temp:** 0°C to +40°C  
**Limited Product Warranty:** 5 Years

ELECTRICAL SPECIFICATIONS

**Input Voltage:** 100-240VAC                      **Input Frequency:** 42 ~ 63Hz                      **Short Circuit Protection:** Auto Recovery.  
**Driver Certifications:** c-RU-us Class 2,                      The output shall return to normal when the  
FCC Part 15 Class B, RoHS                      fault condition is removed.

PHYSICAL SPECIFICATIONS

**Mounting:** Wall mounted - Single Gang                      **Housing Material:** PC Plastic w/  
Box (supplied by others)                      glass/acrylic faceplate

SHIPPING INFORMATION

**OrderingCode(s):** TLCN-CWRGBW30-BK                      **Box Quantity:** 1                      **Box Dimensions (L-W-H):** 140x85x52 mm