


Project:	
Location:	
Model#: ROL5330K-24V-SS1	Туре:
Client:	Qty:
Prepared by:	Date:

### **SERIES SPECIFICATIONS**




Highlight architectural features or add emphasis to landscaping. The IP67 rated a die-cast Aluminium housing make this fixture built to last. Suitable for dimming with Tamlite controls.



### PERFORMANCE SPECIFICATIONS

## **Luminance Distribution Chart**



Initial Lumen Output: 10lm
Ambient Operating Temp: -20C to +40C


Environmental Rating(s): IP67 Limited Product Warranty: 3 Year(s) **UL Classification:** Wet Location Listed



Project:	
Location:	
Model#: ROL5330K-24V-SS1	Туре:
Client:	Qty:
Prepared by:	Date:

### LED SPECIFICATIONS

## SPD



Source Type: LED Colour Temperature: 3000K

### **ELECTRICAL SPECIFICATIONS**

Input Voltage: 24Vdc

**Over Temperature Protection:** Auto recovery. Current returns to normal after

over temperature is removed.

Fixture Draw: 3W

Dimming: Suitable for dimming with

**Tamlite Controls** 

## PHYSICAL SPECIFICATIONS

Finish Colour: Chrome Plated Stainless

Steel

Housing Material: Die-cast Aluminium

Wiring: IP67 rated connections by others

Mounting: Recessed In-ground

# SHIPPING INFORMATION

OrderingCode(s): ROL5330K-24V-SS1

Box Weight: .750 kg

**Box Quantity: 1** 

Box Dimensions (L-W-H): 125 x 125 x

125 mm



Project:	
Location:	
Model#: ROL5330K-24V-SS1	Туре:
Client:	Qty:
Prepared by:	Date:

# LINE DRAWING

# **Line Drawings**

