



Project:	
Location:	
Model#: DL6MED/SL/IC	Type:
Client:	Qty:
Prepared by:	Date:

#### SERIES SPECIFICATIONS

To supply and install Tamlite DL6MED Series of line voltage recessed slope Housing as specified. The Housing shall operate at 120VAC. Lamps shall be as specified, medium base lamps up to a maximum of the rated lamp wattage on the fixture nameplate. The lamps shall not be supplied with the fixture. The fixture shall be c-UL-us approved.

#### PERFORMANCE SPECIFICATIONS

**NEMA Type:** IC Rated  
**Limited Product Warranty:** 1 Year

**Environmental Rating(s):** IC Rated, Air  
Tight ASTM E283

**UL Classification:** Damp Location Listed

#### LED SPECIFICATIONS

**Source Type:** Incandescent

#### ELECTRICAL SPECIFICATIONS

**Input Voltage:** 120-277Vac

**Input Frequency:** 60 Hz

**Max Operating Case Temperature:** 90°C

#### PHYSICAL SPECIFICATIONS

**Finish Colour:** Galvanized  
**Mounting:** Compression Clamp

**Finish Type:** Galvanized Steel  
**Housing Material:** Galvanized Steel

**Wiring:** 7x 7/8" Knockouts

#### SHIPPING INFORMATION

**OrderingCode(s):** DL6MED/SL/IC  
**Carton Weight:** 13lbs/5.9Kgs

**Carton Quantity:** 4

**Carton Dimensions (I-W-H):**  
610x489x222mm