

Project:	
Location:	
Model#: TLCR45030K-347V	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

recessed potlights as well as ceiling mounted Speakers and Fans to prevent



PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 4,718 lm
Environmental Rating(s): IP20
CCN Number: IFAM7.E359675

Efficacy: 102.27 lm/W
UL Classification: Dry Location Only
Limited Product Warranty: 5 Years

Luminaire Type: Semi-Direct
Ambient Operating Temp: -20°C to +40°C

LED SPECIFICATIONS

Source Type: LED
Colour Temperature: 3120K

CRI: >80
Chromaticity: x=0.4299; y=0.4039

L70: > 50,000Hrs
Duv: 0.0009

ELECTRICAL SPECIFICATIONS

Driver Manufacturer: Antron
Fixture Draw: 046.13 W
Dimming: 1-10Vdc

Input Voltage: 347VAC
Short Circuit Protection: Auto Recovery.
 The output shall return to normal when the fault condition is removed.

Input Frequency: 60Hz
THD @ 120VAC(%): 12.58%
Driver Certifications: c-RU-us Class 2, FCC Part 15 Class B, RoHS

PHYSICAL SPECIFICATIONS

Finish Colour: White
Mounting: Surface, Suspended
Lens Type: Frosted Prismatic

Finish Type: Textured Powder Coat over Chromate Conversion Coat
Housing Material: Heavy Gauge Steel
Reflector Material: Painted Steel

Wiring: Back and End Knock outs with luminaire disconnect
Lens Material: PMMA



Project:	
Location:	
Model#: TLCR45030K-347V	Type:
Client:	Qty:
Prepared by:	Date:

SHIPPING INFORMATION

OrderingCode(s): TLCR45040K-UN4

Carton Quantity: 6

Box Quantity: 1

Carton Dimensions (L-W-H):
1230x385x235mm

Box Dimensions (L-W-H): 1210x213x73
mm