

Project:		
Location:		
Model#: AR-N7S	Type:	
Client:	Qty:	
Prepared by:	Date:	

SERIES SPECIFICATIONS



To supply JL-240 series of twist-lock photocontrol receptacles, designed for the fixtures intended to have an ANSI C136.10-2006 receptacle to fit a twist-lock photocontrol. This series conforms to ANSI C136.41-2013 to allow a LED lamp multi-controlled through the receptacle. This series offers 2 or 4 gold-plated low voltage pads on the top surface to fit photocontrols that have ANSI C136.41 conforming spring contacts, and offers male quick connectors at the rear/back for signal connection. This series also offers 360 degree rotation limiting feature to conforming to ANSI C136.10 requirements. Both JL-240X and JL-240Y have been recognized, and JL-200Z14 has been listed by UL to applicable US and Canadian safety standards, under file E188110, Vol.1 & Vol.2.NEMA-7 Twist lock receptacle to be used with the Tamlite ARPS, ARPT and ARWP series of fixtures



IP44



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP44

Ambient Operating Temp: -40C to +70C

UL Classification: Locking Type

Photocontrols UL773

Certification Standards: UL Safety US-CA

Sound Transmission Class Rating:

Limited Product Warranty: 1 year

LED SPECIFICATIONS

Input Voltage: 120~480Vac

Input Frequency: 50-60Hz

Fixture Draw: 1.5W

ELECTRICAL SPECIFICATIONS

Input Voltage: 120~480Vac

Input Frequency: 50-60Hz

Fixture Draw: 1.5W

Dimming: 0-10Vdc, (0% Min Light Level)

PHOTOCELL SENSOR INFORMATION

Finish Colour: Black

EMERGENCY INFORMATION

Wiring: Internal

Housing Material: Plastic

PHYSICAL SPECIFICATIONS

Finish Colour: Black

Wiring: Internal

Housing Material: Plastic

SHIPPING INFORMATION

OrderingCode(s): AR-N7

Box Weight: 0.09 kg

Box Quantity: 1

Box Dimensions (L-W-H): 84 x 66 x 80
mm