



Project:	
Location:	
Model#: AR-Spike	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply TamLite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.




PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA **CCN Number:** IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1 **Box Weight:** 0.5kg
Line Drawings



Series Architecture

Part	Wattage	CCT	Mounting	Optics	Voltage	Finish	Accessories
ARPS	35: 35W	30K: 3000K	SD: SD Pole Mount	T2: Type II	UNV: 120-277VAC	BZ: Bronze [shown]	None
	T5: 75W	40K: 4000K	3R: 3' RD Pole	T24: with House Side Shield	UN4: 347VAC	BK: Black O	Occupancy Sensor
	140: 140W	50K: 5000K	4R: 4' RD Pole	T3: Type III		WH: White	AR-N3PC-UNV 120VAC Photo control
	185: 185W	AM: Amber	5R: 5' RD Pole	T34: with House Side Shield		CC: Custom	AR-N3PC-UN4 347VAC Photo control
			SF: Slip Filter	T4: Type IV			AR-SPK6 Dist. Optics Programming remote, sold separately
				T44: with House Side Shield			FBR-100
				T5: Type V			
				T54: with House Side Shield			

SHIPPING INFORMATION

Box Quantity: 1 **Box Weight:** 0.5kg

Project:	
Location:	
Model#: AR-Spike	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

