



Project:	
Location:	
Model#: AR-Spike	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply TamLite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.




PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA **CCN Number:** IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1 **Box Weight:** 0.5kg

Line Drawings



Series Architecture

Part	Wattage	CCT	Mounting	Optics	Voltage	Finish	Accessories
ARPS	35/ 35W	30K/ 3000K	SD 50 Pole Mount	T2 Type II	UNV 120-277VAC	BZ Bronze [shown]	None
	T5 75W	40K 4000K	3R 3' RD Pole	T24 with House Side Shield	UN4 347VAC	BK Black	O Occupancy Sensor
	140 140W	50K 5000K	4R 4' RD Pole	T3 Type III		WH White	AR-N3PC-UNV 120VAC Photo control
	185 185W	AM Amber	5R 5' RD Pole	T34 with House Side Shield		CC Custom	AR-N3PC-UN4 347VAC Photo control
			SF Slip Filter	T4 Type IV			AR-SPKE Dist Spike
				T44 with House Side Shield			Programming remote, sold separately
				T5 Type V			FBR-100
				T54 with House Side Shield			

SHIPPING INFORMATION

Box Quantity: 1 **Box Weight:** 0.5kg

Project:	
Location:	
Model#: AR-Spike	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

