

Project:	
Location:	
Model#: TLDD105K-120-GY	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply Tamlite TLDD Series of outdoor LED Dusk to Dawn Fixture as specified. The luminaire shall operate at 120Vac and use a NICHIA® Approved Driver. The housing shall be constructed of powder coated die-cast aluminum with a gasketed polycarbonate lens. A durable formed gasket shall be provided between the enclosure and the lens. All parts shall be corrosion resistant. The LEDs shall be supplied with the luminaire. The fixture shall be c-Ulus approved and DLC Listed.




PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 1059lmEfficacy: 116.3lm/WBeam Angle: 110 degUL Classification: Wet Location ListedCertification Standards: UL Safety US-DLC Number: P9JMQZAF

Limited Product Warranty: 5 Year(s) CA , DLC

LED SPECIFICATIONS

SPD



Source Type: LED **CRI:** >70 **L70:** 60000 Hrs

Colour Temperature: 5000K Chromaticity: x=0.34612 y=0.35242 Colour Tolerance: 5 SDCM

Duv: 0.001



Project:	
Location:	
Model#: TLDD105K-120-GY	Туре:
Client:	Qty:
Prepared by:	Date:

ELECTRICAL SPECIFICATIONS

Input Voltage: 120Vac Current Draw@ 120Vac: 0.0759A Dimming: Not Suitable for Dimming Input Frequency: 50-60Hz Power Factor @120Vac: 0.99 Fixture Draw: 9.11W
THD @ 120Vac(%): >15%

PHYSICAL SPECIFICATIONS

Finish Colour: Grey

Housing Material: Die-cast Aluminium

Finish Type: Textured powder coat over chromate conversion coat

Lens Material: Polycarbonate

Mounting: 1/2" threaded octagon box mount

Lens Type: Frosted

SHIPPING INFORMATION

OrderingCode(s): TLDD105K-120-GY

Box Weight: 1.0 kg **Carton Weight:** 8.5 kg

Box Quantity: 1 Carton Quantity: 8 Box Dimensions (L-W-H): 215 \times 145 \times

140 mm

Carton Dimensions (I-W-H): 460 x 320 x

320 mm