

Project:	
Location:	
Model#: TLDD105K-120-GY	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply TamLite TLDD Series of outdoor LED Dusk to Dawn Fixture as specified. The luminaire shall operate at 120Vac and use a NICHIA® Approved Driver. The housing shall be constructed of powder coated die-cast aluminum with a gasketed polycarbonate lens. A durable formed gasket shall be provided between the enclosure and the lens. All parts shall be corrosion resistant. The LEDs shall be supplied with the luminaire. The fixture shall be c-ULus approved and DLC Listed.




PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 1059lm	Efficacy: 116.3lm/W	Beam Angle: 110 deg
UL Classification: Wet Location Listed	Certification Standards: UL Safety US-CA	DLC Number: P9JMQZAF
Limited Product Warranty: 5 Year(s)	, DLC	

LED SPECIFICATIONS

SPD



Source Type: LED	CRI: >70	L70: 60000 Hrs
Colour Temperature: 5000K	Chromaticity: x=0.34612 y=0.35242	Colour Tolerance: 5 SDCM
Duv: 0.001		



Project:	
Location:	
Model#: TLDD105K-120-GY	Type:
Client:	Qty:
Prepared by:	Date:

ELECTRICAL SPECIFICATIONS

Input Voltage: 120Vac
Current Draw @ 120Vac: 0.0759A
Dimming: Not Suitable for Dimming

Input Frequency: 50-60Hz
Power Factor @ 120Vac: 0.99

Fixture Draw: 9.11W
THD @ 120Vac(%): >15%

PHYSICAL SPECIFICATIONS

Finish Colour: Grey
Housing Material: Die-cast Aluminium

Finish Type: Textured powder coat over chromate conversion coat
Lens Material: Polycarbonate

Mounting: 1/2" threaded octagon box mount
Lens Type: Frosted

SHIPPING INFORMATION

OrderingCode(s): TLDD105K-120-GY

Box Weight: 1.0 kg
Carton Weight: 8.5 kg

Box Quantity: 1
Carton Quantity: 8

Box Dimensions (L-W-H): 215 x 145 x 140 mm
Carton Dimensions (I-W-H): 460 x 320 x 320 mm