

Project:	
Location:	
Model#: AR-PSSF	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply Tamlite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA


CCN Number: IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1

Box Weight: 2 kg

Line Drawings



Series Architecture

ARPS									
Part	Wattage	CCT	Mounting	Optics	Voltage	Finish	Accessories	Note	
ARPS	35 70W	3000K	80° 2" RD Pole	T2	UNV 120-277VAC	BZ Black	[None]		
	70 72W	4000K	80° 2" RD Pole	T2H with House Side Shield	UN4 347VAC	BR Black	Occupancy Sensor		
	140 140W	5000K	48° 4" RD Pole	T3	Type III	WH White	AR-APC-UNV	120VAC Photo control	
	185 185W	AM Amber	58° 12" RD Pole	T3H with House Side Shield		CC Custom	AR-APC-UN4	247VAC Photo control	
			SF Slip Filter	T4	Type IV	AR-SPIKE		Bird Spike	
				T4H with House Side Shield		FSR-100		Programming remote, sold separately	
				T5	Type V				
				T5H with House Side Shield					

SHIPPING INFORMATION

Box Quantity: 1

Box Weight: 2 kg

Project:	
Location:	
Model#: AR-PSSF	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

