

Project:	
Location:	
Model#: AR-PSSF	Type:
Client:	Qty:
Prepared by:	Date:

## SERIES SPECIFICATIONS



To supply Tamlite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

## PERFORMANCE SPECIFICATIONS

**Certification Standards:** UL Safety US-CA


**CCN Number:** IFAM7.E359675

## PHYSICAL SPECIFICATIONS

**Box Quantity:** 1

**Box Weight:** 2 kg

**Line Drawings**



## Series Architecture

ARPS									
Part	Wattage	CCT	Mounting	Optics	Voltage	Finish	Accessories		
ARPS	35 35W	30K 3000K	SQ SO Pole Mount	T2 Type II	UNV 120-277VAC	BZ Bronze	[blank]	None	
	75 75W	40K 4000K	SR 1" RD Pole	T2H with House Side Shield	UN4 347VAC	BL Black	O	Occupancy Sensor	
	140 140W	50K 5000K	4R 4" RD Pole	T3 Type III		WH White	AR-NDSPC-UNV	120VAC Photo control	
	185 185W	AM Amber	5R 5" RD Pole	T3H with House Side Shield		CO Custom	AR-NDSPC-UN4	347VAC Photo control	
			SF Slip Filter	T4 Type IV			AR-SPKE	Bird Spike	
				T4H with House Side Shield			FBR-100	Programming remote, sold separately	
				T5 Type V					
				T5H with House Side Shield					

## SHIPPING INFORMATION

**Box Quantity:** 1

**Box Weight:** 2 kg

Project:	
Location:	
Model#: AR-PSSF	Type:
Client:	Qty:
Prepared by:	Date:

## LINE DRAWING

### Line Drawings

