

Project:	
Location:	
Model#: AR-PSSF	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply TamLite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA


CCN Number: IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1

Box Weight: 2 kg

Line Drawings



Series Architecture

Part	Watts	CCT	Mounting	Optics	Voltage	Finish	Accessories
ARPS	35 35W	30K 3000K	SD 50 Pole Mount	T2 Type II	UN4 120-277VAC	BZ Bronze [shown]	None
	T5 75W	40K 4000K	3R 3' RD Pole	T24 with House Side Shield	UN4 347VAC	BK Black	Occupancy Sensor
	140 140W	50K 5000K	4R 4' RD Pole	T3 Type III		WH White	AR-N3PC-UNV 120VAC Photo control
	185 185W	AM Amber	5R 5' RD Pole	T34 with House Side Shield		CC Custom	AR-N3PC-UN4 347VAC Photo control
			SF Slip Filter	T4 Type IV			AR-SPKE Dist. Optics
				T44 with House Side Shield			Programming remote, sold separately
				T5 Type V			
				T54 with House Side Shield			

SHIPPING INFORMATION

Box Quantity: 1

Box Weight: 2 kg

Project:	
Location:	
Model#: AR-PSSF	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

