

Project:							
Location:							
Model#: AR-PSSF	Туре:						
Client:	Qty:						
Prepared by:	Date:						

SERIES SPECIFICATIONS



To supply Tamlite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

PERFORMANCE SPECIFICATIONS


Certification Standards: UL Safety US- CCN Number: IFAM7.E359675

CA

PHYSICAL SPECIFICATIONS

Box Quantity: 1 Box Weight: 2 kg

Line Drawings



Series Architecture

ARPS	··							·								
Part	Wattage		сст		Mounting		Optics		Voltage		Finish		Accessories			
ARPS	35	35W	30K	3000K	SQ	SQ Pole Mount	T2	Type II	UNV	120-277VAC	BZ	Bronze	[blank]	None		
	75	75W	40K	4000K	3R	3" RD Pole	T2H	with House Side Shield	UN4	347VAC	вк	Black	0	Occupancy Sensor		
	140	140W	50K	5000K	4R	4" RD Pole	T3	Type III			WH	White	AR-N3PC-UNV	120VAC Photo control		
	185	185W	AM	Amber	5R	5" RD Pole	T3H	with House Side Shield			CC	Custom	AR-N3PC-UN4	347VAC Photo control		
					SF	Slip Fitter	T4	Type IV					AR-SPIKE	Bird Spike		
							T4H	with House Side Shield					FSIR-100	Programming remote, sold seperately		
							T5	Type V								
							T5H	with House Side Shield								

SHIPPING INFORMATION

Box Quantity: 1 Box Weight: 2 kg



Project:						
Location:						
Model#: AR-PSSF	Туре:					
Client:	Qty:					
Prepared by:	Date:					

LINE DRAWING

Line Drawings

