

Project:	
Location:	
Model#: AR-PSSQ	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS




To supply TamLite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA **CCN Number:** IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1 **Box Weight:** 2 kg
Line Drawings



Series Architecture

Part	Wattage	CCT	Mounting	Optics	Voltage	Finish	Accessories
ARPS	35/ 35W	30K/ 3000K	SD 30 Pole Mount	T2 Type II	UNV 120-277VAC	BZ Bronze (shown)	None
	T5 75W	40K/ 4000K	3R 3' RD Pole	T2H with House Side Shield	UN4 347VAC	BK Black	Occupancy Sensor
	140/ 140W	50K/ 5000K	4R 4' RD Pole	T3 Type III		WH White	AR-N3PC-LINV 120VAC Photo control
	185/ 185W	AM Amber	5R 5' RD Pole	T3H with House Side Shield		CC Custom	AR-N3PC-LIN4 347VAC Photo control
			SF Slip Filter	T4 Type IV			AR-SPKE Dist Opia
				T4H with House Side Shield			Programming remote, sold separately
				T5 Type V			
				T5H with House Side Shield			

SHIPPING INFORMATION

Box Quantity: 1 **Box Weight:** 2 kg

Project:	
Location:	
Model#: AR-PSSQ	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

