

Project:		
Location:		
Model#: AR-PSSQ	Type:	
Client:	Qty:	
Prepared by:	Date:	

SERIES SPECIFICATIONS



To supply Tamlite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA


CCN Number: IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1

Box Weight: 2 kg

Line Drawings



Series Architecture

ARPS									
Part	Voltage	CCT	Mounting	Optics	Voltage	Finish	Accessories		
ARPS-35 35W	35W	30K 5000K	8Q SQ Pole Mount	T2 Type II	UNV 120-277VAC	BZ Bronze	[blank]	None	
75 75W	75W	30K 4000K	8Q SQ Pole Mount	T2H with House Side Shield	UNV 247VAC	BR Brushed	AR-SPKE	120VAC Photo sensor	
140 140W	65W	5000K	4R 4" RD Pole	T3 Type III		WH White	AR-APC-UNV	AR-APC-UNV	
185 185W	AM Amber		5R 5" RD Pole	T3H with House Side Shield		CC Custom	AR-APC-UN4	347VAC Photo control	
			SF Slip Filter	T4 Type IV			AR-SPKE	AR-SPKE	
				T4H with House Side Shield				Bird Spike	
				T5 Type V				Programming remote, sold separately	
				T5H with House Side Shield			FSIR-100		

SHIPPING INFORMATION

Box Quantity: 1

Box Weight: 2 kg

LINE DRAWING

Line Drawings

