

Project:	
Location:	
Model#: AR-PSWM	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply TamLite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

PERFORMANCE SPECIFICATIONS

Certification Standards: UL Safety US-CA

CCN Number: IFAM7.E359675

PHYSICAL SPECIFICATIONS

Box Quantity: 1

Box Weight: 2 kg

Series Architecture

ARPS									
Part	Wattage		CCT		Mounting		Optics		Accessories
ARPS	35	35W	30K	3000K	SQ	SQ Pole Mount	T2	Type II	[blank] None
	75	75W	40K	4000K	3R	3" RD Pole	T2H	with House Side Shield	Occupancy Sensor
	140	140W	50K	5000K	4R	4" RD Pole	T3	Type III	120VAC Photo control
	185	185W	AM	Amber	5R	5" RD Pole	T3H	with House Side Shield	347VAC Photo control
					SF	Slip Fitter	T4	Type IV	AR-N3PC-UNV AR-SPIKE Bird Spike
							T4H	with House Side Shield	Programming remote, sold separately
							T5	Type V	
							T5H	with House Side Shield	

SHIPPING INFORMATION

Box Quantity: 1

Box Weight: 2 kg