

Project:	
Location:	
Model#:	AR-PSWM
Client:	Qty:
Prepared by:	Date:

## SERIES SPECIFICATIONS



To supply Tamlite ARPS Series of LED fixtures as specified. The luminaire shall operate at and use a dimmable, constant current type driver. The housing shall be constructed of with a . All hardware to be stainless steel. Bottom access wiring compartment to be hinged and sealed with a durable foamed gasket. Fixtures to come standard with a NEMA7 style twist lock socket and shorting cap. Optics to be constructed of be sealed via captive gasket and complete with a LED's shall be as specified with a colour tolerance. Fixture shall be UL Safety US-CA listed.

## PERFORMANCE SPECIFICATIONS

**Certification Standards:** UL Safety US-CA

**CCN Number:** IFAM7.E359675

## PHYSICAL SPECIFICATIONS

**Box Quantity:** 1

**Box Weight:** 2 kg

### Series Architecture

ARPS		Wattage		CCT		Mounting		Optics		Voltage		Finish		Accessories	
ARPS	35	35W	30K	3000K	SQ	SQ Pole Mount	T2	Type II	UNV	120-277VAC	BZ	Bronze	[blank]	None	
	75	75W	40K	4000K	3R	3" RD Pole	T2H	with House Side Shield	UN4	347VAC	BK	Black	O	Occupancy Sensor	
	140	140W	50K	5000K	4R	4" RD Pole	T3	Type III			WH	White	AR-N3PC-UNV	120VAC Photo control	
	185	185W	AM	Amber	5R	5" RD Pole	T3H	with House Side Shield			CC	Custom	AR-N3PC-UN4	347VAC Photo control	
					SF	Slip Fitter	T4	Type IV					AR-SPIKE	Bird Spike	
							T4H	with House Side Shield					FSIR-100	Programming remote, sold seperately	
							T5	Type V							
							T5H	with House Side Shield							

## SHIPPING INFORMATION

**Box Quantity:** 1

**Box Weight:** 2 kg