

Project:		
Location:		
Model#: EVK3-4A-BK	Туре:	
Client:	Qty:	
Prepared by:	Date:	

SERIES SPECIFICATIONS



To supply Tamlite DLELV Series of Tamper Proof Elevator Cab Lights as specified. The kit shall operate at 120Vac. Lamps shall be as specified, LED MRI6 lamps with a GU5.3 base. Lamps are not included in the kit. Driver shall be included, and as specified 12VDC constant voltage, with a maximum output of 48W. The driver shall be cULus Listed



PERFORMANCE SPECIFICATIONS			
Luminaire Type: Direct Ambient Operating Temp: 0C to +40C	Environmental Rating(s): IP20 Certification Standards: cULus	UL Classification: Dry Location Only Limited Product Warranty: 1 Year	
LED SPECIFICATIONS			
Source Type: MR16, GU5.3 base	CRI: >70		
ELECTRICAL SPECIFICATIONS			
Input Voltage: 120Vac Dimming: Not Suitable for Dimming	Input Frequency: 50-60Hz	Fixture Draw: 48W	
PHYSICAL SPECIFICATIONS			
Finish Colour: Black Mounting: Recessed	Finish Type: Anodized Housing Material: Aluminium	Wiring: 106" wiring harness (47" driver to first fixture, 30" between fixtures)	
SHIPPING INFORMATION			
OrderingCode(s): EVK3-4A-BK Box Weight: 0.7 kg Carton Weight: 14.8 1	Box Quantity: 1 Carton Quantity: 20	Box Dimensions (L-W-H): 152 x 127 x 132 mm Carton Dimensions (I-W-H): 620 x 270 x 320 mm	



Project:	
Location:	
Model#: EVK3-4A-BK	Туре:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings



SERIES ARCHITECTURE

Optional Extras: EVK-4A-DRIVER, EVK-ADAPTER, EVK-HARNESS, EVK-RS