

Project:	
Location:	
Model#: CMS2BZ	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



LED security floodlights are ideal for entrances, walkways, yards, driveways, and patios. Fixture mounts to a recessed junction box on wall or ceiling. Adjustable heads allow for precision aiming.















PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Isolux Diagram



Initial Lumen Output: 2120lm Certification Standards: cETLus, UL-773A Efficacy: 68.8lm/W

Limited Product Warranty: 3 Year(s)


Max Candela: 896cd



Project:	
Location:	
Model#: CMS2BZ	Туре:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

SPD



Source Type: LED

Colour Temperature: 4000K

CRI: >70

L70: 40000 Hrs

Fixture Draw: 32W

ELECTRICAL SPECIFICATIONS

Input Voltage: 120Vac Input Frequency: 50-60Hz

Current Draw@ 120Vac: 0.2667 Dimming: 0-10Vdc, (0% Min Light Level)

PHYSICAL SPECIFICATIONS

Finish Colour: Bronze (RAL-8019) Mounting: 4" Junction Box Housing Material: Polycarbonate

Lens Material: Polycarbonate Lens Type: Frosted

SHIPPING INFORMATION

OrderingCode(s): CMS2BZ

Carton Quantity: 12 Box Quantity: 1 Box Dimensions (L-W-H): 192 x 175 x

Carton Dimensions (I-W-H): 541 x 400 x 160mm

338mm

SERIES ARCHITECTURE

Optional Extras: CMS180BZ