

Project:	
Location:	
Model#: TRRMSCS2180BZ	Туре:
Client:	Qty:
Prepared by:	Date:

### **SERIES SPECIFICATIONS**



LED security floodlights are ideal for entrances, walkways, yards, driveways, and patios. Fixture mounts to a recessed junction box on wall or ceiling. Adjustable heads allow for precision aiming. White CCT can be adjusted on the sensor head.















### PERFORMANCE SPECIFICATIONS

### **Luminance Distribution Chart**



# Isolux Diagram



Initial Lumen Output: 2400lm Certification Standards: cETLus, UL-773A Efficacy: 75lm/W

Limited Product Warranty: 3 Year(s)

Max Candela: 975cd



Project:	
Location:	
Model#: TRRMSCS2180BZ	Туре:
Client:	Qty:
Prepared by:	Date:

### LED SPECIFICATIONS

**Source Type:** LED **CRI:** >70 **L70:** 40000 Hrs

Colour Temperature: 3000K~5000K

### **ELECTRICAL SPECIFICATIONS**

Input Voltage: 120Vac Input Frequency: 50-60Hz Fixture Draw: 32W

Current Draw@ 120Vac: 0.2667 Dimming: 0-10Vdc, (0% Min Light Level)

### OCCUPANCY SENSOR INFORMATION

Sensor Type: Passive Infrared (PIR) -

Outdoor

Programing Type: Dials on Body

Control Type: On-Off

Input Voltage: 120Vac

## PHOTOCELL SENSOR INFORMATION

**Control Type:** On-Off Input Voltage: 120Vac Programing Type: Dials on Body, Manual

over-ride at night

### PHYSICAL SPECIFICATIONS

Finish Colour: Bronze (RAL-8019) Mounting: 4" Junction Box Housing Material: Polycarbonate

Lens Material: Polycarbonate Lens Type: Frosted

# SHIPPING INFORMATION

OrderingCode(s): TRRMSCS2180BZ

**Box Quantity: 1**