

Project:	
Location:	
Model#: SM71430K-120-WH	Type:
Client:	Qty:
Prepared by:	Date:


SERIES SPECIFICATIONS

To supply and install Tamlite SM7 series of LED fixtures as specified




PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Isolux Diagram



Zonal Lumen Summary

Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens
0-10	30.96	30-40	160.27	60-70	110.72	90-100	0	120-130	0	150-160	0
10-20	88.49	40-50	165.31	70-80	60.9	100-110	0	130-140	0	160-170	0
20-30	133.6	50-60	148.2	80-90	14.76	110-120	0	140-150	0	170-180	0

Project:	
Location:	
Model#: SM71430K-120-WH	Type:
Client:	Qty:
Prepared by:	Date:

Initial Lumen Output: 919 lm

Beam Angle: 110 deg

Environmental Rating(s): IP20

Certification Standards: cULus, Energy Star

Efficacy: 62.55 lm/W

Field Angle: 160 deg

UL Classification: Damp Location Listed

Limited Product Warranty: 5 Years


CBCP: 328 cd

Luminaire Type: Surface

Ambient Operating Temp: 0°C to +40°C

LED SPECIFICATIONS

SPD



Source Type: LED

Colour Temperature: 3000K

Manufacturer:

Duv: 0.000592

CRI: >70

ELECTRICAL SPECIFICATIONS

Input Voltage: 120 Vac

Current Draw@ 120Vac: 0.1279 A

Over Temperature Protection: Auto

Recovery, The fixture shall shut down and return to operation when the temperature returns to normal.

Input Frequency: 50-60 Hz

Power Factor @120Vac: >.90

Short Circuit Protection: Auto Recovery.

The output shall return to normal when the fault condition is removed.

Fixture Draw: 14 W

Dimming: Triac - ELV - Incandescent

Driver Certifications: c-RU-us Class 2, FCC Part 15 Class B, RoHS

PHYSICAL SPECIFICATIONS

Finish Colour: White

Housing Material: Aluminium

Reflector Material: Acrylic

Finish Type: Textured powder coat over chromate conversion coat

Lens Material: PMMA

Mounting: Surface

Lens Type: Frosted

Project:	
Location:	
Model#: SM71430K-120-WH	Type:
Client:	Qty:
Prepared by:	Date:

SHIPPING INFORMATION

OrderingCode(s): SM71430K-120-WH

Box Weight: 0.5 kg

Carton Weight: 10.13

Box Quantity: 1

Carton Quantity: 24

Box Dimensions (L-W-H): 203 x 203 x 53
mm

Carton Dimensions (L-W-H): 623 x 420 x
245 mm

LINE DRAWING

Line Drawings

