
Project:	
Location:	
Model#: PET-JT-SWD-WH	**Type:**
Client:	**Qty:**
Prepared by:	**Date:**

SERIES SPECIFICATIONS

To supply Tamlite's PET-JT for the PET Series of linear luminaires.



PERFORMANCE SPECIFICATIONS


Beam Angle: 100 deg
Spacing Criteria: 1.22 (0-180) 1.2 (90-270)
Certification Standards: UL Safety US-CA

Field Angle: 156 deg
Environmental Rating(s): IP20
CCN Number: IFAM7.E359675

Luminaire Type: Suspended Direct
UL Classification: Dry Location Only
Limited Product Warranty: 5 Year(s)

LED SPECIFICATIONS

SPD



Source Type: LED

L90: > 50,000 hrs.

Colour Temperature: 3000K, 3500K, 4000K, 5000K Field Selectable

ELECTRICAL SPECIFICATIONS

Dimming: 0-10Vdc, (0% Min Light Level)

Over Temperature Protection: Auto recovery. The output recovers when the temperature returns to normal.

Short Circuit Protection: Auto recovery. The output recovers when short is removed.

© March 28th 2024 Tamlite Lighting Canada. All rights reserved. Specifications are subject to change without notice. Consult manufacturer for latest version of this specification sheet. Tamlite Lighting | 7805 HWY 50, VAUGHAN, ON. L4H 3N5 | Tel: (905) 495-4432 | Fax: (905) 495-3494 | www.tamlite.ca

Project:	
Location:	
Model#: PET-JT-SWD-WH	**Type:**
Client:	**Qty:**
Prepared by:	**Date:**

PHYSICAL SPECIFICATIONS

Finish Colour: White
Lens Material: Polycarbonate

Finish Type: Electrostatic Polyester Powder Coat
Lens Type: Opal

Housing Material: Aluminium

SHIPPING INFORMATION

OrderingCode(s): PET-JT-SWD-WH

Box Quantity: 1

© March 28th 2024 Tamlite Lighting Canada. All rights reserved. Specifications are subject to change without notice. Consult manufacturer for latest version of this specification sheet. Tamlite Lighting | 7805 HWY 50, VAUGHAN, ON. L4H 3N5 | Tel: (905) 495-4432 | Fax: (905) 495-3494 | www.tamlite.ca