

Project:	
Location:	
Model#: WPA1004K-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS




To supply TamLite's WPA series of LED fixtures as specified. The luminaire shall operate at 347Vac, and use a constant current type driver. The housing shall be constructed of powder-coated die-cast Aluminium with a hinged wiring compartment, and an impact resistant polycarbonate lens. A durable formed gasket shall be provided between the enclosure and the lens, and the wiring compartment and housing. Internal wiring shall terminate in quick connects for ease of connectivity. The reflector shall be made of highly specular material and contoured to maximize light output efficiency. All parts shall be corrosion resistant. LEDs shall be as specified, LUXEON® 2835 LED Chips. The LEDs shall be supplied with the luminaire. The luminaire shall be cULus Listed and DLC Listed.



PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Maximum Candela = 5091.216 Located At Horizontal Angle = 0, Vertical Angle = 11
 # 1 - Vertical Plane Through Horizontal Angles (90 - 270)
 # 2 - Vertical Plane Through Horizontal Angles (0 - 180)

Project:	
Location:	
Model#: WPA1004K-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

Zonal Lumen Summary

ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS
0-10	463.67	40-50	2107.58	80-90	85.59	120-130	32.76	160-170	20.60
10-20	1354.09	50-60	1549.96	90-100	12.38	130-140	36.60	170-180	7.47
20-30	2050.56	60-70	926.71	100-110	18.04	140-150	35.73	--	--
30-40	2336.11	70-80	408.37	110-120	25.81	150-160	30.18	--	--

Initial Lumen Output: 12134lm

Luminaire Type: Cut-off

UL Classification: Wet Location Listed

CCN Number: IFAM7.E359675

Efficacy: 114.77lm/W

BUG Rating: B3-U0-G1

Ambient Operating Temp: -40C to +40C

Limited Product Warranty: 5 Year(s)


Max Candela: 5063

Environmental Rating(s): IP65

Certification Standards: UL Safety US-CA , DLC

LED SPECIFICATIONS

SPD



Source Type: LED

CRI: >80

Chromaticity: x=0.3799 y=0.3774

Manufacturer: Lumileds®

L70: 54000 Hrs

Duv: 0.0005

Part Number: LUXEON 2835

Colour Temperature: 4000K



Project:	
Location:	
Model#: WPA1004K-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

ELECTRICAL SPECIFICATIONS

Driver Manufacturer: Inventronics®
Input Frequency: 50-60Hz
Inrush Current: 2.17 A2S
THD @347Vac(%): <10%
Dimming: 1-10Vdc, (10% Min Light Level)
Short Circuit Protection: Auto Recovery.
The output shall return to normal after the fault condition is removed.

Driver Part Number: ESD-096S360DT
Fixture Draw: 100.2W
Max On-Delay: < 1 S
Driver MTBF: 211,000hrs
Dimming Current mA: 300mA
Driver Certifications: c-RU-us Class 2, FCC Part 15 Class B, RoHS

Input Voltage: 347Vac
Current Draw@347Vac: 0.2899
Power Factor @347Vac: >.90
Max Operating Case Temperature: 90C
Over Temperature Protection: Decreases output current, returning to normal after over temperature is removed.

PHYSICAL SPECIFICATIONS

Finish Colour: Black (RAL-9011)
Mounting: Wall Mount
Lens Type: Clear Optics

Finish Type: Textured Powder Coat over Chromate Conversion Coat
Housing Material: ADC12 Aluminium
Reflector Material: highly specular material

Wiring: 3 x ½" Coin Plugs, one each side and bottom
Lens Material: PMMA

SHIPPING INFORMATION

OrderingCode(s): WPA1004K-UN4-BK
Box Weight: 5.08 kg
Carton Weight: 10.7

Box Quantity: 1
Carton Quantity: 2

Box Dimensions (L-W-H): 315 x 165 x 355 mm
Carton Dimensions (I-W-H): 345 x 330 x 370 mm



Project:	
Location:	
Model#: WPA1004K-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

SERIES ARCHITECTURE

Series Architecture

WPA NOMENCLATURE

Part	Wattage		CCT		Mounting		Voltage		Colour		Accessories	
WPA	12	12W	3K	3000K	[Blank]	Wall Surface	UNV	120-277VAC	BZ	Bronze	PC	WPFLED-PC120
	30	30W	4K	4000K			347	347VAC	BK	Black		
	50	50W	5K	5000K					WT	White		
	80	80W							CC	Custom Colour		
	100	100W										
	120	120W										