

Project:	
Location:	
Model#: AAFL12RGBWY-30D-24V	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



Highlight architectural features or add emphasis to landscaping with the efficiency and flexibility of RGBW LED technology. Select from millions of colour combinations including 3000K white. The IP65 rated die-cast Aluminium housing make this fixture built to last.



PERFORMANCE SPECIFICATIONS

Beam Angle: 30 deg **UL Classification:** Wet Location Listed **Limited Product Warranty:** 3 Year(s)

LED SPECIFICATIONS

Source Type: LED **Colour Temperature:** RGB-W(5000K)

ELECTRICAL SPECIFICATIONS

Input Voltage: 24Vdc **Fixture Draw:** 12.00 W **Max On-Delay:** < 1S
Over Temperature Protection: Auto recovery. Current returns to normal after over temperature is removed.

PHYSICAL SPECIFICATIONS

Wiring: 1M - 5 conductor tail **Mounting:** Yoke Mounting **Housing Material:** Die-cast Aluminium


SHIPPING INFORMATION

OrderingCode(s): AAFL12RGBWY-30D-24V **Box Quantity:** 1

Project:	
Location:	
Model#: AAFL12RGBWY-30D-24V	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings



SERIES ARCHITECTURE

Series Architecture

AAFL -													
Part	Wattage		Colour		Mounting	Optics		Voltage		Finish		Options	
AAFL	12	12W	RGBW3	Red, Green, Blue, White (3000K)	Y Yoke	8	8 Degree	120	120Vac	BZ	Black	TY Tuya Control ⁽¹⁾⁽²⁾	
	36	36W				15	15 Degree	24	24Vdc ⁽³⁾	BK	Bronze		
	72	72W	RGBW5	Red, Green, Blue, White (5000K)		25	25 Degree			WH	White		
						30	30 Degree			CC	Custom		
						40	40 Degree						

1) Suitable for 120Vac versions only

2) Tuya phone app (iPhone or Android) by others

3) See Low Voltage Controls for more details

2022-11-17



Download the APP "TUYASMART" and register a new account or log in with an existing account.