

Project:	
Location:	
Model#: SM1224-SW-120-WH	Type:
Client:	Qty:
Prepared by:	Date:


## SERIES SPECIFICATIONS

To supply TamLite SM12 series of LED fixtures as specified




## PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Isolux Diagram



Zonal Lumen Summary

Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens
0-10	63.46	30-40	328.55	60-70	226.97	90-100	0	120-130	0	150-160	0
10-20	181.41	40-50	338.88	70-80	124.84	100-110	0	130-140	0	160-170	0
20-30	273.87	50-60	303.82	80-90	30.25	110-120	0	140-150	0	170-180	0

Total Initial Lumen Output; 1872.05 lm



Project:	
Location:	
Model#: SM1224-SW-120-WH	Type:
Client:	Qty:
Prepared by:	Date:

#### Co-efficient of Utilization

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RF	20				20				20			20			20			20
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	95	98	94	92	94	91	89	90	88	86	84
2	99	91	84	78	96	89	83	77	85	80	76	82	78	74	79	75	72	70
3	90	80	72	65	88	78	71	65	75	69	63	72	67	62	70	65	61	59
4	83	71	62	55	80	69	61	55	67	60	54	64	58	53	62	57	53	50
5	76	63	54	47	74	62	54	47	60	52	47	58	51	46	56	50	46	44
6	70	57	48	41	68	56	47	41	54	47	41	52	46	41	51	45	40	38
7	65	52	43	37	63	51	42	36	49	42	36	48	41	36	46	40	36	34
8	61	47	38	33	59	46	38	33	45	38	32	44	37	32	43	36	32	30
9	57	43	35	29	55	43	35	29	41	34	29	40	34	29	39	33	29	27
10	53	40	32	27	52	39	32	27	38	31	26	37	31	26	36	30	26	24

**Initial Lumen Output:** 1872lm

**CBCP:** 672 CD

**UL Classification:** Damp Location Listed

**Limited Product Warranty:** 5 year(s)

**Efficacy:** 78lm/W

**Luminaire Type:** Direct - Surface Mount

**Certification Standards:** cETLus

**Max Candela:** 672cd

**Environmental Rating(s):** IP20

**CCN Number:** 4007670

#### LED SPECIFICATIONS

**Source Type:** LED

**CRI:** >80

**Colour Temperature:** 3000K, 4000K or 5000K Field Selectable

#### ELECTRICAL SPECIFICATIONS

**Input Voltage:** 120Vac

**Current Draw at 120Vac:** 0.2000A

**Dimming:** Triac, Reverse Phase

**Driver Certifications:** c-RU-us Class 2, FCC Part 15 Class B, RoHS

**Input Frequency:** 50/60 hz

**Max On-Delay:** < 1s

**Over Temperature Protection:** Auto Recovery, The fixture shall shut down and return to operation when the temperature returns to normal.

**Fixture Draw:** 24W

**Power Factor at 120Vac:** > 0.9

**Short Circuit Protection:** Auto Recovery. The output shall return to normal when the fault condition is removed.

#### PHYSICAL SPECIFICATIONS

**Finish Colour:** White

**Housing Material:** High Grade Plastic

**Reflector Material:** Acrylic

**Finish Type:** Injection molded colour

**Lens Material:** PMMA

**Entries:** One (1), Back Mount

**Mounting::** Surface, back mount

**Lens Type:** Diffused

Project:	
Location:	
Model#: SM1224-SW-120-WH	Type:
Client:	Qty:
Prepared by:	Date:

## SHIPPING INFORMATION

OrderingCode(s): SM1224-SW-IP20

Carton Quantity: 10

Box Quantity: 1

Carton Dimensions (L-W-H):


47.2cm(18.58")\*34.1cm(13.43")\*32.9cm(12.95")

Box Dimensions (L-W-H):

4.7cm(1.8")\*34.1cm(13.43")\*32.9cm(12.95")

## LINE DRAWING

### Line Drawings





Project:	
Location:	
Model#: SM1224-SW-120-WH	Type:
Client:	Qty:
Prepared by:	Date:

## SERIES ARCHITECTURE

### Series Architecture

SM	-	12	-	24	-	sw		-	120	-	WH		-		
Part	Size			Wattage		Colour			Voltage		Finish		Mounting Options		
SM	12	12 inch		24	24W	SW	Selectable White			120	120Vac	WH	White	blank	Flush Mount
							3000K, 4000K, 5000K							SFM	Semi Flush Mount

2022-12-02