

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Type:
Client:	Qty:
Prepared by:	Date:

## SERIES SPECIFICATIONS

To supply Tamllite Constant Voltage Power Supply, compatible with Triac dimmers. Forward phase or Reverse phase, though Reverse is preferred. The plastic body is suitable for dry locations. This power supply will work with all Tamllite Low Voltage Lighting Systems products. The driver shall be UL/cUL listed, Class 2, Class P, Type HL approval.



## PERFORMANCE SPECIFICATIONS

**Environmental Rating(s):** IP20

**Certification Standards:** UL/cUL listed, Class 2, Class P, Type HL approval

**UL Classification:** Dry Location Only

**Limited Product Warranty:** 7 Year(s)

**Ambient Operating Temp:** -40C to 40C

## ELECTRICAL SPECIFICATIONS

**Input Voltage:** 120~277Vac

**Current Draw@ 120Vac:** 0.5

**Power Factor @120Vac:** >.98%

**Over Temperature Protection:** 100C  
±10C shut down o/p voltage, automatically recover after cooling.

**Input Frequency:** 50-60Hz

**Inrush Current:** 7A, 50%, 420us

**Power Factor @277Vac:** >.98%

**Short Circuit Protection:** 120VAC Hiccup mode, recovers automatically after fault condition is removed

**Fixture Draw:** 36W

**Max On-Delay:** < 1 s

**Dimming:** Triac. Reverse or Forward Phase

## PHYSICAL SPECIFICATIONS

**Finish Colour:** Plastic

**Mounting:** Screw mount by others

**Finish Type:** White

**Housing Material:** Plastic

**Wiring:** 18 AWG by others

## SHIPPING INFORMATION

**OrderingCode(s):** CV36W-24V/IP20-SN/T

**Box Weight:** 0.21 kg

**Box Quantity:** 1

**Carton Quantity:** 50

**Box Dimensions (L-W-H):** 261 x 31 x 21 mm

**Carton Weight:** 10.5 kg

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Type:
Client:	Qty:
Prepared by:	Date:

## LINE DRAWING

### Line Drawings

