

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply Tamlite Constant Voltage Power Supply, compatible with Triac dimmers. Forward phase or Reverse phase, though Reverse is preferred. The plastic body is suitable for dry locations. This power supply will work with all Tamlite Low Voltage Lighting Systems products. The driver shall be UL/cUL listed, Class 2, Class P, Type HL approval.



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP20	UL Classification: Dry Location Only	Ambient Operating Temp: -40C to 40C
Certification Standards: UL/cUL listed, Class 2, Class P, Type HL approval	Limited Product Warranty: 7 Year(s)	

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac	Input Frequency: 50/60 Hz	Fixture Draw: 36.00 W
Current Draw at 120Vac: 00.5000A	Inrush Current: 7A, 50%, 420us	Max On-Delay: < 1S
Power Factor at 120Vac: > 0.95	Power Factor at 277Vac: > 0.95	Dimming: Triac. Reverse or Forward Phase
Over Temperature Protection: 100C ??10C shut down o/p voltage, automatically recover after cooling.	Short Circuit Protection: 120VAC Hiccup mode, recovers automatically after fault condition is removed	

PHYSICAL SPECIFICATIONS

Finish Colour: Plastic	Finish Type: White	Wiring: 18 AWG by others
Mounting: Screw mount by others	Housing Material: Plastic	

SHIPPING INFORMATION

OrderingCode(s): CV36W-24V/IP20-SN/T	Box Quantity: 1	Box Dimensions (L-W-H): 261 x 31 x 21 mm
Box Weight: 0.21 kg	Carton Quantity: 50	Carton Weight: 10.5 kg

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

