

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply Tamlite Constant Voltage Power Supply, compatible with Triac dimmers. Forward phase or Reverse phase, though Reverse is preferred. The plastic body is suitable for dry locations. This power supply will work with all Tamlite Low Voltage Lighting Systems products. The driver shall be UL/cUL listed, Class 2, Class P, Type HL approval.



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP20

Certification Standards: UL/cUL listed, Class 2, Class P, Type HL approval

UL Classification: Dry Location Only

Limited Product Warranty: 7 Year(s)

Ambient Operating Temp: -40C to 40C

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac

Current Draw at 120Vac: 00.5000A

Power Factor at 120Vac: > 0.95

Over Temperature Protection: 100C

??10C shut down o/p voltage, automatically recover after cooling.

Input Frequency: 50/60 Hz

Inrush Current: 7A, 50%, 420us

Power Factor at 277Vac: > 0.95

Short Circuit Protection: 120VAC Hiccup mode, recovers automatically after fault condition is removed

Fixture Draw: 36.00 W

Max On-Delay: < 1S

Dimming: Triac. Reverse or Forward Phase

PHYSICAL SPECIFICATIONS

Finish Colour: Plastic

Mounting: Screw mount by others

Finish Type: White

Housing Material: Plastic

Wiring: 18 AWG by others

SHIPPING INFORMATION

OrderingCode(s): CV36W-24V/IP20-SN/T

Box Weight: 0.21 kg

Box Quantity: 1

Carton Quantity: 50

Box Dimensions (L-W-H): 261 x 31 x 21 mm

Carton Weight: 10.5 kg

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

