

Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Туре:
Client:	Qty:
Prepared by:	Date:

### **SERIES SPECIFICATIONS**



To supply Tamlite Constant Voltage Power Supply, compatible with Triac dimmers. Forward phase or Reverse phase, though Reverse is preferred. The plastic body is suitable for dry locations. This power supply will work with all Tamlite Low Voltage Lighting Systems products. The driver shall be UL/cUL listed, Class 2, Class P, Type HL approval.







#### PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP20
Certification Standards: UL/cUL listed,
Class 2, Class P, Type HL approval

**UL Classification:** Dry Location Only **Limited Product Warranty:** 7 Year(s)

Ambient Operating Temp: -40C to 40C

# **ELECTRICAL SPECIFICATIONS**

Input Voltage: 120~277Vac
Current Draw@ 120Vac: 0.5
Power Factor @120Vac: >.98%
Over Temperature Protection: 100C
±10C shut down o/p voltage, automatically

recover after cooling.

Input Frequency: 50-60Hz
Inrush Current: 7A, 50%, 420us
Power Factor @277Vac: >.98%
Short Circuit Protection: 120VAC Hiccup

mode, recovers automatically after fault

condition is removed

Fixture Draw: 36W Max On-Delay: < 1 s

Dimming: Triac. Reverse or Forward

Phase

### PHYSICAL SPECIFICATIONS

Finish Colour: Plastic

Mounting: Screw mount by others

Finish Type: White
Housing Material: Plastic

Wiring: 18 AWG by others

## SHIPPING INFORMATION

OrderingCode(s): CV36W-24V/IP20-SN/T

Box Weight: 0.21 kg

Box Quantity: 1
Carton Quantity: 50

Box Dimensions (L-W-H): 261 x 31 x 21

mm

Carton Weight: 10.5 kg



Project:	
Location:	
Model#: CV36W-24V-IP20-SN-T	Туре:
Client:	Qty:
Prepared by:	Date:

## LINE DRAWING

## **Line Drawings**

