

Project:	
Location:	
Model#: CV36W-24V-IP67-SL-T	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply Tamlite Constant Voltage Power Supply, compatible with Triac dimmers. Forward phase or Reverse phase, though Reverse is preferred. The aluminum body is suitable for wet locations. This power supply will work with all Tamlite Low Voltage Lighting Systems products. The driver shall be UL/cUL listed, Class 2, Class P, Type HL approval.



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP67	UL Classification: Wet Location Listed	Ambient Operating Temp: -40C to 40C
Certification Standards: UL/cUL listed, Class 2, Class P, Type HL approval	Limited Product Warranty: 7 Year(s)	

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac	Input Frequency: 50/60 Hz	Fixture Draw: 36.00 W
Current Draw at 120Vac: 00.5000A	Inrush Current: 7A, 50%, 420us	Max On-Delay: < 1S
Power Factor at 120Vac: > 0.95	Power Factor at 277Vac: > 0.95	Dimming: Triac. Reverse or Forward Phase
Over Temperature Protection: 100C ??10C shut down o/p voltage, automatically recover after cooling.	Short Circuit Protection: 120VAC Hiccup mode, recovers automatically after fault condition is removed	

PHYSICAL SPECIFICATIONS

Finish Colour: Aluminium	Finish Type: Dark Grey	Wiring: 18 AWG three conductor input, 18 AWG two conductor output
Mounting: Screw mount by others	Housing Material: Aluminium	

SHIPPING INFORMATION

OrderingCode(s): CV36W-24V/IP67-SL/T	Box Quantity: 1	Box Dimensions (L-W-H): 271 x 50 x 23 mm
Box Weight: 0.3 kg	Carton Quantity: 30	Carton Dimensions (I-W-H): 290 x 270 x 160 mm
Carton Weight: 9 kg		

Project:	
Location:	
Model#: CV36W-24V-IP67-SL-T	Type:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

