

Project:		
Location:		
Model#:	CV36W-24V-IP67-SL-T	Type:
Client:		Qty:
Prepared by:		Date:

SERIES SPECIFICATIONS



To supply Tamlite Constant Voltage Power Supply, compatible with Triac dimmers. Forward phase or Reverse phase, though Reverse is preferred. The aluminum body is suitable for wet locations. This power supply will work with all Tamlite Low Voltage Lighting Systems products. The driver shall be UL/cUL listed, Class 2, Class P, Type HL approval.



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP67

Certification Standards: UL/cUL listed, Class 2, Class P, Type HL approval

UL Classification: Wet Location Listed

Limited Product Warranty: 7 Year(s)

Ambient Operating Temp: -40C to 40C

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac

Current Draw at 120Vac: 0.05000A

Power Factor at 120Vac: > 0.95

Over Temperature Protection: 100C ±10C

shut down o/p voltage, automatically recover after cooling.

Input Frequency: 50/60 Hz

Inrush Current: 7A, 50%, 420us

Power Factor at 277Vac: > 0.95

Short Circuit Protection: 120VAC Hiccup mode, recovers automatically after fault condition is removed

Fixture Draw: 36.00 W

Max On-Delay: < 1S

Dimming: Triac. Reverse or Forward Phase

PHYSICAL SPECIFICATIONS

Finish Colour: Aluminium

Mounting: Screw mount by others

Finish Type: Dark Grey

Housing Material: Aluminium

Wiring: 18 AWG three conductor input, 18

AWG two conductor output

SHIPPING INFORMATION

OrderingCode(s): CV36W-24V/IP67-SL/T

Box Weight: 0.3 kg

Carton Weight: 9 kg

Box Quantity: 1

Carton Quantity: 30

Box Dimensions (L-W-H): 271 x 50 x 23

mm

Carton Dimensions (L-W-H): 290 x 270 x

160 mm

LINE DRAWING

Line Drawings

