

Project:						
Location:						
Model#: HBM150SW-WRV-BK	Туре:					
Client:	Qty:					
Prepared by:	Date:					

SERIES SPECIFICATIONS



To supply the Tamlite HBM Series selectable white LED high bay luminaire as specified. The luminaire shall operate at 120-347Vac. The fixture is 0-10Vdc dimmable with optional sensor. Wattage is field selectable to three levels. CCT is filed selectable to three levels. The housing shall be constructed of aluminum with a prismatic lense. LEDs shall be as specified Lumileds® LED chips. The luminaire shall be cULus Listed.





















PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Isolux Diagram



Zonal Lumen Summary

Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens
0-10	1053.75	30-40	5791.91	60-70	847.51	90-100	0.4	120-130	2.32	150-160	3.51
10-20	3059.11	40-50	4101.35	70-80	316.87	100-110	0.76	130-140	3.32	160-170	2.44
20-30	4767.01	50-60	1939.17	80-90	42.91	110-120	1.31	140-150	3.75	170-180	0.86

Total Initial Lumen Output; 21938.26 Im



Project:							
Location:							
Model#: HBM150SW-WRV-BK	Туре:						
Client:	Qty:						
Prepared by:	Date:						

Co-efficient of Utilization

RC		80				7	70		50		30			10		0		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RF		2	0			2	0			20			20			20		20
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	90
2	104	98	92	88	101	96	91	87	92	88	85	89	86	83	86	84	81	79
3	97	88	82	76	94	87	81	76	84	79	75	81	77	73	79	75	72	70
4	90	80	73	67	88	79	72	67	76	71	66	74	69	65	72	68	64	62
5	84	73	65	60	82	72	65	59	70	64	59	68	62	58	66	61	58	56
6	78	66	59	53	76	66	58	53	64	57	53	62	57	52	61	56	52	50
7	73	61	53	48	71	60	53	48	59	52	48	57	52	47	56	51	47	45
8	68	56	49	43	67	55	48	43	54	48	43	53	47	43	52	47	43	41
9	64	52	45	40	63	51	44	39	50	44	39	49	43	39	48	43	39	37
10	60	48	41	36	59	48	41	36	47	40	36	46	40	36	45	40	36	34

Initial Lumen Output: 21937lm

CBCP: 11122cd
Luminaire Type: Direct

UL Classification: Wet Location Listed **CCN Number:** IFAM7.E359675

Efficacy: 145.62lm/W
Beam Angle: 120 deg

Spacing Criteria: 1.32(0-180) 1.32(90-270)

Ambient Operating Temp: -40C to +50C Limited Product Warranty: 5 Year(s)

Max Candela: 11122cd (270 h, 3V)

Field Angle: 170 deg

Environmental Rating(s): IP65

Certification Standards: UL Safety US-

CA, DLC



Project:						
Location:						
Model#: HBM150SW-WRV-BK	Туре:					
Client:	Qty:					
Prepared by:	Date:					


LED SPECIFICATIONS

R Tables

R1	83
R2	90
R3	94
R4	83
R5	83
R6	85
R7	87
R8	68

R9	17
R10	75
R11	82
R12	61
R13	85
R14	97
R15	78
Ra	85

TM-30



Source Type: LED CRI: >80

L70: > 54000 hrs.

Manufacturer: Lumileds®

Rf: 84

L90: 50,000 hrs.

Part Number: L128

Rg: 96

Colour Temperature: Selectable White

(3500K, 4000K, 5000K)



Project:						
Location:						
Model#: HBM150SW-WRV-BK	Туре:					
Client:	Qty:					
Prepared by:	Date:					

ELECTRICAL SPECIFICATIONS

Driver Manufacturer: Sosen
Input Frequency: 50/60 hz
Current Draw at 347Vac: 0.4323A
Power Factor at 120Vac: > 0.95
THD at 347Vac(%): < 10%
Surge Suppression: 6KV

Over Temperature Protection: Auto Recovery, The fixture shall shut down and return to operation when the temperature

returns to normal.

Driver Part Number: SS-150M-XXXX **Fixture Draw:** 150W (100,80,50W)

Inrush Current: 70 A2S
Power Factor at 347Vac: > 0.95
Driver MTBF: 200,000 hrs

Dimming: 0-10Vdc, (0% Min Light Level) **Short Circuit Protection:** Auto Recovery. The output shall return to normal when the

fault condition is removed.

Input Voltage: 120-347Vac Current Draw at 120Vac: 1.2500A

Max On-Delay: < 0.5 S THD at 120Vac(%): < 10%

Max Operating Case Temperature: 90C

Dimming Current mA: 0.11

Driver Certifications: c-RU-us Class 2,

FCC Part 15 Class B, RoHS

PHYSICAL SPECIFICATIONS

Finish Colour: Black

Mounting: 1/2" NPS Threaded fitting, Loop

standard

Lens Type: Refractor

Finish Type: Textured powder coat over

chromate conversion coat

Housing Material: Die-cast Aluminium

Weight: 2.9 kg

Wiring: 3M length, UL STW 18#/3C, -40

+105°C, 600V, Black

Lens Material: Polycarbonate

SHIPPING INFORMATION

OrderingCode(s): HBM150SW-UN4-BK

Box Weight: 3.9 kg **Box Quantity:** 1 **Box Dimensions (L-W-H):** 355 x 355 x


185 mm




Project:						
Location:						
Model#: HBM150SW-WRV-BK	Туре:					
Client:	Qty:					
Prepared by:	Date:					


LINE DRAWING

Line Drawings











Project:						
Location:						
Model#: HBM150SW-WRV-BK	Туре:					
Client:	Qty:					
Prepared by:	Date:					


SERIES ARCHITECTURE

Series Architecture

<u>HBM</u>								
Part	Wat	tage	ССТ		Voltage		Finis	h
HBM	150	150W	SW	Selectable White	WRV	120-347VAC	BK	Black
	240	240W		3500K, 4000K, 5000K				

Options	
HBM-REF	Refractor
HBM-ACR	Lense
HBM-YKBK	Yoke Mount (B, C, D) Sizing
HBM-HOOK	Mounting Hook with Safety Screw
HBM-PM	3/4" NPS Threaded Mount

Power Consumption vs LumenOutput			
	150W	100W	80W
3500K	21,105	14,070	11,256
4000K	21,937	14,625	11,700
5000K	21,750	14,500	11,600



Optional Extras: HBM-REF(Acrylic refractor), HBM-ACR(Acrylic Lense), HBM-OC(Occupancy Sensor), HBM-OCREM(Occupancy sensor remote programmer), HBM-YK(Surface Mount Yoke), HBM-PM(3/4" NPT Adapter), HBM-HOOK(3/4" NPT Adapter)