

Project:	
Location:	
Model#: TLP14SMK-WH	Type:
Client:	Qty:
Prepared by:	Date:

## SERIES SPECIFICATIONS

To supply Tamlite flat panel surface mounting kit.



## PERFORMANCE SPECIFICATIONS

**Environmental Rating(s):** IP20

**UL Classification:** Dry Location Only

**Certification Standards:** cULus

## PHYSICAL SPECIFICATIONS

**Finish Colour:** White

**Finish Type:** Powder Coated

**Mounting:** Surface

**Housing Material:** Aluminium

## SHIPPING INFORMATION

**OrderingCode(s):** TLP14SMK-WH

**Box Weight:** 12.5 kg

**Box Quantity:** 1

**Box Dimensions (L-W-H):** 1320 x 415 x

**Carton Weight:** 12.5

**Carton Quantity:** 2

140 mm

**Carton Dimensions (I-W-H):** 1320 x 415 x

140 mm

LINE DRAWING

**Line Drawings**



## SERIES ARCHITECTURE

### Series Architecture

#### TLPE Nomenclature

Part	Size		Wattage		CCT		Mounting		Voltage		Finish	
TLPE	14	1x4ft	36	36W	30K	3000K	[blank]	T-Bar	UNV	120-277VAC	WH	White
	22	2x2ft	40	40W	35K	3500K	DF	Drywall Flange	UN4	347VAC		
	24	2x4ft	48	48W	40K	4000K	SF	Surface Mount				
			60	60W	50K	5000K	SU	Suspended				

**Optional Extras:** TLP14SPK Suspension kit