

| Project: | |
|---------------------|-------|
| Location: | |
| Model#: DL6MED_IC_R | Туре: |
| Client: | Qty: |
| Prepared by: | Date: |

SERIES SPECIFICATIONS

To supply Tamlite DL6MED Series of line voltage recessed Housing as specified. The Housing shall operate at 120Vac. Lamps shall be as specified, medium base lamps up to a maximum of the rated lamp wattage on the fixture nameplate. The lamps shall not be supplied with the fixture. The fixture shall be c-UL-us approved.



PERFORMANCE SPECIFICATIONS

NEMA Type: IC Rated Environmental Rating(s): IC Rated, Air

Certification Standards: cULus Tight ASTM E283

Limited Product Warranty: 1 Year

UL Classification: Damp Location Listed

LED SPECIFICATIONS

Source Type: Incandescent

ELECTRICAL SPECIFICATIONS

Input Voltage: 120Vac Input Frequency: 50-60Hz Max Operating Case Temperature: 90C

PHYSICAL SPECIFICATIONS

Finish Colour: Galvanized Finish Type: Galvanized Steel Wiring: 7x 7/8" Knockouts

Mounting: Compression Clamp Housing Material: Galvanized Steel

SHIPPING INFORMATION

OrderingCode(s): DL6MED/IC/R Carton Quantity: 6 Carton Dimensions (I-W-H): 533 x 508 x

Carton Weight: 4.3 203 mm