

Project:	
Location:	
Model#: TASLL3BZ	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply Tamlite's TASLL Series of LED Step Light Luminaire as specified. The Luminaire shall operate at 120Vac. The face plate shall be constructed of powder coated steel. The lens shall be either vertical louvered, horizontal louvered or open diffused. LEDs shall be as specified Hongli LED chips. The luminaire shall be c-UL-us listed.








PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart

Isolux Diagram




Initial Lumen Output: 29lm **UL Classification:** Dry Location Listed Max Candela: 11cd Certification Standards: cULus Environmental Rating(s): IP44 Limited Product Warranty: 1 year



Project:	
Location:	
Model#: TASLL3BZ	Туре:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

SPD



Source Type: LED Colour Temperature: 3000K

ELECTRICAL SPECIFICATIONS

Input Voltage: 120Vac Input Frequency: 50-60Hz Fixture Draw: .75W

Current Draw@ 120Vac: 0.0100A

PHYSICAL SPECIFICATIONS

Finish Colour: Bronze Finish Type: Powder Coat Mounting: Recessed J-Box Mount

SHIPPING INFORMATION

OrderingCode(s): TASLL3BZ Box Quantity: 1 Box Dimensions (L-W-H): 77 x 44 x 120

Box Weight: .23 kg Carton Quantity: 24
Carton Weight: 5.4 kg

Carton Dimensions (I-W-H): $270 \times 250 \times$

245 mm



Project:	
Location:	
Model#: TASLL3BZ	Туре:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

