

Project:	
Location:	
Model#: WPG8040K-347V-BK	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS




To supply TamLite WPG series of LED fixtures as specified. The luminaire shall operate at 347Vac, and use a CITIZEN® approved driver. The housing shall be constructed of powder-coated Aluminium with a hinged bolt-on case for replacement access and a tempered glass lens. A durable formed gasket shall be provided between the enclosure and the lens. The reflector shall be made of highly specular material and contoured to maximize light output efficiency. All parts shall be corrosion resistant. LEDs shall be as specified, CITIZEN® CLU038-1208 LED Chips. The LEDs shall be supplied with the luminaire. The luminaire shall be cULus Listed.




PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Maximum Candela = 4645.76 Located At Horizontal Angle = 360, Vertical Angle = 45
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180)
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)
 # 3 - Horizontal Cone Through Vertical Angle (45) (Through Max. Cd.)

Isolux Diagram



TamLite Lighting
 QWP80-4K-UNV
 76W 120-277VAC LED GLASS PACK

Horizontal Footcandles
 Scale: 1 inch = 15 Ft
 Light Loss Factor = 1.00
 Lumens Per Lamp = 9004.2
 Total Lamp Lumens = 9004.2
 Mounting Height = 15.00 Ft
 Maximum Calculated Value = 9.04 Fc
 Arrangement: Single



Project:	
Location:	
Model#: WPG8040K-347V-BK	Type:
Client:	Qty:
Prepared by:	Date:

Zonal Lumen Summary

ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS
0-10	176.02	40-50	1337.78	80-90	904.77	120-130	93.11	160-170	5.34
10-20	462.9	50-60	1298.95	90-100	556.97	130-140	69.77	170-180	0.44
20-30	643.81	60-70	1105.83	100-110	190.89	140-150	47.32	--	--
30-40	946.13	70-80	1024.81	110-120	112.51	150-160	21.89	--	--

Initial Lumen Output: 99976lm

Luminaire Type: Wall Pack Non-Cut-off

Ambient Operating Temp: -40C to +40C

CCN Number: IFAM7.E359675

Efficacy: 129.7lm/W

Environmental Rating(s): IP65

Certification Standards: cETLus, DLC

Limited Product Warranty: 5 Year(s)


Max Candela: 4645

UL Classification: Wet Location Listed

DLC Number: YYYYDPE

LED SPECIFICATIONS

SPD



Source Type: LED

CRI: > 80

Chromaticity: x=0.3460 y=0.3580

Manufacturer: Citizen®

L70: 102000 Hrs

Duv: 0.0029

Part Number: CLU038-1208

Colour Temperature: 4000K



Project:	
Location:	
Model#: WPG8040K-347V-BK	Type:
Client:	Qty:
Prepared by:	Date:

ELECTRICAL SPECIFICATIONS

Driver Manufacturer: IPP

Fixture Draw: 76.92W

THD @347Vac(%): <10%

Dimming: 1-10Vdc, (10% Min Light Level)

Driver Certifications: c-RU-us Class 2,
FCC Part 15 Class B, RoHS

Input Voltage: 277~480Vac

Current Draw@347Vac: 0.2340775815635

Driver MTBF: 50,000hrs

Over Temperature Protection: Auto
Recovery, The fixture shall shut down and
return to operation when the temperature
returns to normal.

Input Frequency: 50-60Hz

Power Factor @347Vac: >.90

Max Operating Case Temperature: 90C

Short Circuit Protection: Auto Recovery.
The output shall return to normal when the
fault condition is removed.

PHYSICAL SPECIFICATIONS

Finish Colour: Black

Mounting: Wall Mount

Lens Type: Clear - Prismatic

Finish Type: Textured powder coat over
chromate conversion coat

Housing Material: ADC12 Aluminium

Reflector Material: Specular Aluminium

Wiring: Internal Connections

Lens Material: Glass

Entries: (3) ½ inch threaded knockouts

SHIPPING INFORMATION

OrderingCode(s): WPG805K-347V-BK

Box Weight: 5.2 kg

Carton Weight: 20.07

Box Quantity: 1

Carton Quantity: 4

Box Dimensions (L-W-H): 370 x 245 x
205 mm

Carton Dimensions (I-W-H): 510 x 385 x
410 mm

SERIES ARCHITECTURE

Series	Wattage	CCT	Voltage	Finish
WPG	40 (40W)	SW (Selectable)	UNV (120-277V)	BZ (Bronze)
	80 (80W)	30K (3000K)	347V (347V)	BK (Black)
	120 (120W)	40K (4000K)	WRV (120-347V)	WH (White)
		50K (5000K)		XX (other)

Optional Extras: Cut off Shield