


| | |
|------------------------|-------|
| Project: | |
| Location: | |
| Model#: TLCR45050K-UN4 | Type: |
| Client: | Qty: |
| Prepared by: | Date: |

SERIES SPECIFICATIONS




To supply TamLite TLCR series of LED Wrap fixtures as specified. The luminaire shall operate at 347Vac. The housing shall be constructed of powder-coated aluminum with a heat and impact resistant tempered PMMA lens. All parts shall be corrosion resistant. The LEDs shall be supplied with the luminaire. The fixture shall be c-ULus listed.



PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Initial Lumen Output: 4887lm

UL Classification: Dry Location Listed

Limited Product Warranty: 5 Year(s)

Efficacy: 106.11lm/W

Ambient Operating Temp: -20C to +40C


Environmental Rating(s): IP20

Certification Standards: cULus

| | |
|------------------------|-------|
| Project: | |
| Location: | |
| Model#: TLCR45050K-UN4 | Type: |
| Client: | Qty: |
| Prepared by: | Date: |

LED SPECIFICATIONS

SPD



Source Type: LED
Colour Temperature: 5000K

CRI: >80
Chromaticity: x= 0.3391; y= 0.3482

L70: >50000hrs

ELECTRICAL SPECIFICATIONS

Input Voltage: 347Vac
Current Draw@347Vac: 0.4167A
THD @347Vac(%):

Input Frequency: 50-60Hz
Max On-Delay: Dimming: 1-10Vdc, (10%
 Min Light Level)

Fixture Draw: 46.06W
Power Factor @347Vac: >90

PHYSICAL SPECIFICATIONS

Finish Colour: White
Mounting: Surface, Suspended
Lens Type: Frosted Prismatic

Finish Type: Textured Powder Coat
Housing Material: Die-Cast Aluminium

Wiring: Luminaire Disconnect
Lens Material: Acrylic

SHIPPING INFORMATION

OrderingCode(s): TLCR45050K-UN4
Carton Quantity: 6

Box Quantity: 1
Carton Dimensions (L-W-H): 1230 x 385 x
 235mm

Box Dimensions (L-W-H): 1210 x 213 x
 73mm

| | |
|------------------------|-------|
| Project: | |
| Location: | |
| Model#: TLCR45050K-UN4 | Type: |
| Client: | Qty: |
| Prepared by: | Date: |

LINE DRAWING

Line Drawings

