

Project:							
Location:							
Model#: TLG854K-UN4-BK	Туре:						
Client:	Qty:						
Prepared by:	Date:						

SERIES SPECIFICATIONS



To supply Tamlite's TLG Series of LED Garage fixture as specified. The luminaire shall operate at 347Vac. The housing shall be constructed of Die-Cast Aluminium with a powder coat finish over chromate conversion treatment with clear, acrylic lenses. The luminaire shall be wet location listed. LEDs shall be as specified Nichia ® LED chips. The luminaire shall be cULus Listed and DLC Listed.

















PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Maximum Candela = 1655.9 Located At Horizontal Angle = 135, Vertical Angle = 69 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) # 2 - Vertical Plane Through Horizontal Angles (90 - 270)

Isolux Diagram





Project:							
Location:							
Model#: TLG854K-UN4-BK	Туре:						
Client:	Qty:						
Prepared by:	Date:						

Zonal Lumen Summary

ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS	ZONE	LUMENS
0-10	72.08	40-50	687.15	80-90	1321.68	120-130	155.43	160-170	0.32
10-20	209.75	50-60	1013.46	90-100	705	130-140	86.04	170-180	O.1
20-30	335.98	60-70	1352.9	100-110	310.24	140-150	31.02		
30-40	471.72	70-80	1460.7	110-120	174.86	150-160	2.09		

Initial Lumen Output: 8336lm Environmental Rating(s): IP65 Certification Standards: UL Safety US-

CA

Efficacy: 100.08lm/W


UL Classification: Wet Location Listed **CCN Number:** IFAM7.E359675

Luminaire Type: Surface Mount

Ambient Operating Temp: -25C to +40C Limited Product Warranty: 5 Year(s)

LED SPECIFICATIONS

SPD



Source Type: LED L70: 60000 Hrs

Manufacturer: Nichia ®
Colour Temperature: 4000K

CRI: > 75 **Duv:** 0.005



Project:	
Location:	
Model#: TLG854K-UN4-BK	Туре:
Client:	Qty:
Prepared by:	Date:

ELECTRICAL SPECIFICATIONS

Input Voltage: 347Vac
Current Draw@347Vac: 0.2471
THD @347Vac(%): <15%

Short Circuit Protection: Auto recovery. The output shall return to normal when the

fault condition is removed.

Input Frequency: 50-60Hz Max On-Delay: < 1.000S

Dimming: 0-10Vdc, (0% Min Light Level) **Driver Certifications:** c-RU-us Class 2,

FCC Part 15 Class B, RoHS

Fixture Draw: 85W

Power Factor @120Vac: >.90

Over Temperature Protection: Auto
recovery. Current returns to normal after

over temperature is removed.

PHYSICAL SPECIFICATIONS

Finish Colour: Black (RAL-9011)
Housing Material: ADC12 Aluminium

Finish Type: Textured powder coat over

chromate conversion coat **Lens Material:** PMMA

Mounting: Surface Lens Type: Clear

SHIPPING INFORMATION

OrderingCode(s): TLG854K-UN4-BK

Box Quantity: 1 **Box Dimensions (L-W-H):** 435 x 435 x


180 mm




Project:	
Location:	
Model#: TLG854K-UN4-BK	Туре:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings





SERIES ARCHITECTURE

Series Architecture

TLG - 45 - 40K			40K	UNV WH			WH			
Part Wattage CCT			Voltage		Finish		Options			
TLG	45	45W	40K	4000K	UNV	120-277VAC	WH	White	OC	Occupancy Sensor*
	85	85W	50K	5000K	UN4	347VAC	ВК	Black	FSIR-100	*FSIR-100 Programer
							BZ	Bronze		

Optional Extras: Occupancy Sensor, FSIR-100 IR Programmer