

Project:						
Location:						
Model#: PET-SUSKIT6-WH	Туре:					
Client:	Qty:					
Prepared by:	Date:					

SERIES SPECIFICATIONS

To supply Tamlite's PET-SUSKIT6 Suspension set. Kit shall come with two canopies and stainless steel mounting cables. Cables will be independently level able by 1/8" ratcheted hardware supplied.



LISTED 120-347 VAC

PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP20 UL Classification: Dry Location

PHYSICAL SPECIFICATIONS

Finish Colour: Black Housing Material: Steel

SHIPPING INFORMATION

OrderingCode(s): PET-SUSKIT6

Box Quantity: 1



Project:						
Location:						
Model#: PET-SUSKIT6-WH	Туре:					
Client:	Qty:					
Prepared by:	Date:					

SERIES ARCHITECTURE

Series Architecture

PET -												
Series	Le	ength	Wattage		CCT Optics		otics	Wattage		Fini	Finish	
PET	2	2FT	20	20W	SW	Selectable White*	D	Direct	WRV	120-347 VAC	WH	White
	3	3FT	30	30W	30K		DI	Direct-Indirect			BK	Black
	4	4FT	40	40W	35K		A1	Asymetric			CC	Custom
	6	6FT	60	60W	40K							
	8	8FT	80	80W	50K							

^{*} Selectable White; 3000K, 3500K, 4000K or 5000K

Optional Accessories (Ordered Seperately)

PET

10ft Power Cord, 5 conductor White
120degree Selectable White Joiner
L-Shaped Selectable White Joiner
L-Shaped Selectable White Interior Joiner
L-Shaped Selectable White exterior Joiner
T-Shaped Selectable White Joiner
X-Shaped Selectable White Joiner
4ft Louver assembly
4ft Plaster Mud Mounting Kit
4ft Reccessed Mounting Kit
Suspension Kit, 6ft long
T-Bar Mounting Kit
Wall Mounting Kit