

Project:	
Location:	
Model#: PET-SUSKIT6-WH	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply Tamlite's PET-SUSKIT6 Suspension set. Kit shall come with two canopies and stainless steel mounting cables. Cables will be independently level able by 1/8" ratcheted hardware supplied.



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP20 UL Classification: Dry Location

PHYSICAL SPECIFICATIONS

Finish Colour: Black Housing Material: Steel

SHIPPING INFORMATION

OrderingCode(s): PET-SUSKIT6

Box Quantity: 1



Project:	
Location:	
Model#: PET-SUSKIT6-WH	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES ARCHITECTURE

Series Architecture

PET -Series Length Wattage CCT Wattage Optics Finish PET 2 2FT 20 20W SW Selectable White* WRV 120-347 VAC D Direct WH White 3 3FT 30 30W DI Direct-Indirect 30K BK Black 4 4FT 40 40W 35K A1 Asymetric CC Custom 6 6FT 60 60W 40K 8 8FT 80 80W 50K

Optional Accessories (Ordered Seperately)

PET

C10	10ft Power Cord, 5 conductor White
J120-SWD-WH	120degree Selectable White Joiner
JL-SWD-WH	L-Shaped Selectable White Joiner
JL-IN-SWD-WH	L-Shaped Selectable White Interior Joiner
JL-OUT-SWD-W	L-Shaped Selectable White exterior Joiner
JT-SWD-WH	T-Shaped Selectable White Joiner
JX-SWD-WH	X-Shaped Selectable White Joiner
LL4	4ft Louver assembly
MUDKIT4	4ft Plaster Mud Mounting Kit
RECKIT4	4ft Reccessed Mounting Kit
SUSKIT6	Suspension Kit, 6ft long
TBARKIT	T-Bar Mounting Kit
WMKIT	Wall Mounting Kit

^{*} Selectable White; 3000K, 3500K, 4000K or 5000K