



Project:	
Location:	
Model#: PET-SUSKIT6-WH	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply Tamlite's PET-SUSKIT6 Suspension set. Kit shall come with two canopies and stainless steel mounting cables. Cables will be independently level able by 1/8" ratcheted hardware supplied.



PERFORMANCE SPECIFICATIONS

Environmental Rating(s): IP20

UL Classification: Dry Location

PHYSICAL SPECIFICATIONS

Finish Colour: Black

Housing Material: Steel

SHIPPING INFORMATION

OrderingCode(s): PET-SUSKIT6

Box Quantity: 1



Project:	
Location:	
Model#: PET-SUSKIT6-WH	Type:
Client:	Qty:
Prepared by:	Date:

**SERIES ARCHITECTURE**

**Series Architecture**

PET - - - - -

Series	Length	Wattage		CCT		Optics		Wattage		Finish	
PET	2 2FT	20	20W	SW	Selectable White*		D	Direct	WRV	120-347 VAC	WH White
	3 3FT	30	30W	30K			DI	Direct-Indirect			BK Black
	4 4FT	40	40W	35K			A1	Asymetric			CC Custom
	6 6FT	60	60W	40K							
	8 8FT	80	80W	50K							

\* Selectable White; 3000K, 3500K, 4000K or 5000K

**Optional Accessories (Ordered Separately)**

PET -

C10	10ft Power Cord, 5 conductor White
J120-SWD-WH	120degree Selectable White Joiner
JL-SWD-WH	L-Shaped Selectable White Joiner
JL-IN-SWD-WH	L-Shaped Selectable White Interior Joiner
JL-OUT-SWD-WH	L-Shaped Selectable White exterior Joiner
JT-SWD-WH	T-Shaped Selectable White Joiner
JX-SWD-WH	X-Shaped Selectable White Joiner
LL4	4ft Louver assembly
MUDKIT4	4ft Plaster Mud Mounting Kit
RECKIT4	4ft Recessed Mounting Kit
SUSKIT6	Suspension Kit, 6ft long
TBARKIT	T-Bar Mounting Kit
WMKIT	Wall Mounting Kit