












Luminance Distribution Chart




Horizontal FC
 1 2 5 1 2 5 10
 Mtq.Ht. = Grid = 100



Project:	
Location:	
Model#: ARPS353K3RT2H-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

BUG Graph



Initial Lumen Output: 2973lm

BUG Rating: B1-U0-G1

Ambient Operating Temp: -40C to +40C

Limited Product Warranty: 10 Year(s)

Efficacy: 84lm/W

Environmental Rating(s): IP66

Certification Standards: UL Safety US-CA

Luminaire Type: Type II-H - Medium

UL Classification: Wet Location Listed

CCN Number: IFAM7.E359675


Project:	
Location:	
Model#: ARPS353K3RT2H-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

R Tables

R1	73	R9	0
R2	77	R10	46
R3	80	R11	76
R4	76	R12	50
R5	74	R13	73
R6	70	R14	89
R7	80	R15	67
R8	61	--	--

SPD



Source Type: LED
CRI: >70
Chromaticity: x=0.4338 y=0.4030

Manufacturer: Nichia®
L70: 60000 Hrs.
Colour Tolerance: 3 SDCM

Part Number: NVSW219
Colour Temperature: 3000K
Duv: 0.006

ELECTRICAL SPECIFICATIONS

Driver Manufacturer: Inventronics®
Input Frequency: 50/60 hz
Inrush Current: 0.32 A2S
Power Factor at 347Vac: > 0.90
Max Operating Case Temperature: 90C
Dimming Current mA: 0.25 mA
Driver Certifications: c-RU-us Class 2, FCC Part 15 Class B, RoHS

Driver Part Number: LTC-040SxxxDSP
Fixture Draw: 35W
Max On-Delay: < 1 S
THD at 347Vac(%): < 10%
Surge Suppression: 10kV
Over Temperature Protection: Auto recovery. Current returns to normal after over temperature is removed.

Input Voltage: 347Vac
Current Draw at 347Vac: 0.1009
Auxiliary Control: 12 Vdc
Driver MTBF: 459,000 hrs
Dimming: 1-10Vdc, (10% Min Light Level)
Short Circuit Protection: Auto recovery. The output shall return to normal when the fault condition is removed.

PHYSICAL SPECIFICATIONS

Finish Colour: Black (RAL-9011)
Mounting:: 3" round pole
Lens Type: clear optics
Entries: gasketed wire entry

Finish Type: Textured powder coat over chromate conversion coat
Housing Material: ADC12 aluminium
Weight: 4.7 kg

Wiring: internal junction
Lens Material: PMMA
EPA: 1.39 sqft

Project:	
Location:	
Model#: ARPS353K3RT2H-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

SHIPPING INFORMATION

OrderingCode(s): ARPS353KT2H-UN4-BK, AR-PSSQ-BK, AR-PS3R5R-BK


Box Weight: 4.7 kg

Box Quantity: 1

Box Dimensions (L-W-H): 495 x 340 x 180 mm

LINE DRAWING

Line Drawings





Project:	
Location:	
Model#: ARPS353K3RT2H-UN4-BK	Type:
Client:	Qty:
Prepared by:	Date:

SERIES ARCHITECTURE

Series Architecture

ARPS													
Part	Wattage		CCT		Mounting		Optics		Voltage		Finish		Accessories
ARPS	35	35W	30K	3000K	SQ	SQ Pole Mount	T2	Type II	UNV	120-277VAC	BZ	Bronze	[blank]
	75	75W	40K	4000K	3R	3" RD Pole	T2H	with House Side Shield	UN4	347VAC	BK	Black	O
	140	140W	50K	5000K	4R	4" RD Pole	T3	Type III	WRV	120-347VAC	WH	White	AR-N3PC-UNV
	185	185W	AM	Amber	5R	5" RD Pole	T3H	with House Side Shield			CC	Custom	AR-N3PC-UN4
					SF	Slip Fitter	T4	Type IV					AR-SPIKE
							T4H	with House Side Shield					FSIR-100
							T5	Type V					
							T5H	with House Side Shield					

Optional Extras: AR-SPIKE AR-N3PC-UNV