

Project:	
Location:	
Model#: MWP15SW-120-BZ-PC	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



To supply Tamlite MWP15 series of LED fixtures as specified. The body shall be polycarbonate and mount to an aluminum back plate. The LEDs shall be Selectable in CCT. The luminaire shall be cULus listed and DLC qualified














PERFORMANCE SPECIFICATIONS


Luminance Distribution Chart



Initial Lumen Output: 2129lm UL Classification: Wet Location Listed

DLC Number: PLHH3S66Z411

Isolux Diagram



Efficacy: 137.2lm/w

Ambient Operating Temp: -20C to +40C

CCN Number: IFAM7.E359675

Max Candela: 686cd

Certification Standards: UL Safety US-

CA, DLC


Limited Product Warranty: 5 Year(s)




Project:	
Location:	
Model#: MWP15SW-120-BZ-PC	Туре:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

SPD



TM-30



Source Type: LED **CRI:** >80 **L90:** 50,000 Hrs **Duv:** -0.002

Manufacturer: Lumileds

Rf: 83

Colour Temperature: 3000K, 4000K,

5000K Field Selectable

Part Number: L128 3080RA35003H1

Rg: 97

Chromaticity: x=0.3462 y=0.3583



Project:	
Location:	
Model#: MWP15SW-120-BZ-PC	Туре:
Client:	Qty:
Prepared by:	Date:

ELECTRICAL SPECIFICATIONS

Driver Part Number: HB-LPG015G-52

Fixture Draw: 15.52

Dimming: 0-10Vdc, (0% Min Light Level)

Input Voltage: 120Vac

Current Draw@ 120Vac: 0.1250A

Input Frequency: 50-60Hz Power Factor @120Vac: >.90

PHYSICAL SPECIFICATIONS

Housing Material: Aluminium Back Plate Lens Material: Prismatic Polycarbonate

SHIPPING INFORMATION

OrderingCode(s): MWP155K-120-BZ-PC

Box Weight: 1.05kg **Carton Weight:** 11.4kg

Box Quantity: 1
Carton Quantity: 10

Box Dimensions (L-W-H): 154 x 88 x

225mm

Carton Dimensions (I-W-H):

460x325x245mm

LINE DRAWING

Line Drawings

