

'	Project:		
	Location:		
	Model#: MWP155K-120-BZ-PC	Туре:	
	Client:	Qty:	
	Prepared by:	Date:	

SERIES SPECIFICATIONS



To supply Tamlite MWP15 series of LED fixtures as specified. The body shall be polycarbonate and mount to an aluminum back plate. The LEDs shall be 5000K in CCT. The luminaire shall be cETLus and DLC listed.



PERFORMANCE SPECIFICATIONS

Isolux Diagram





Project:	
Location:	
Туре:	
Qty:	
Date:	
_	

Initial Lumen Output: 986lm UL Classification: Wet Location Listed DLC Number: PLHH3S66Z411 Efficacy: 76lm/W Ambient Operating Temp: -20C to +40C CCN Number: IFAM7.E359675 Max Candela: 232cd at H15 V20 Certification Standards: UL Safety US-CA , DLC Limited Product Warranty: 5 Year(s)

LED SPECIFICATIONS





Source Type: LED Colour Temperature: 5000K CRI: >80 Chromaticity: x=0.3462 y=0.3583 L90: 50,000 Hrs

ELECTRICAL SPECIFICATIONS		
Input Voltage: 120Vac Current Draw@ 120Vac: 0.1250A	Input Frequency: 50-60Hz Power Factor @120Vac: >.90	Fixture Draw: 13.04W
PHYSICAL SPECIFICATIONS		
Housing Material: Aluminium Back Plate	Lens Material: Prismatic Polycarbonate	
SHIPPING INFORMATION		
OrderingCode(s): MWP155K-120-BZ-PC Box Weight: 1.48 kg Carton Weight: 6.1 kg	Box Quantity: 1 Carton Quantity: 4	Box Dimensions (L-W-H): 310 x 210 x 125 mm Carton Dimensions (I-W-H): 640 x 440 x 395 mm



Project:	
Location:	
Model#: MWP155K-120-BZ-PC	Туре:
Client:	Qty:
Prepared by:	Date:

LINE DRAWING

Line Drawings

