



| | |
|-------------------|-------|
| Project: | |
| Location: | |
| Model#: HBX100-WG | Type: |
| Client: | Qty: |
| Prepared by: | Date: |

SERIES SPECIFICATIONS

To supply the Tamlite HBX-100 wire guard



ELECTRICAL SPECIFICATIONS

Dimming: 0-10Vdc, (0% Min Light Level)

SHIPPING INFORMATION

OrderingCode(s): HBX100-WG

Box Weight: 0.75 kg

Box Quantity: 1

Box Dimensions (L-W-H): 655 x 295 x 85 mm

SERIES ARCHITECTURE

Series Architecture

| HBX - - - - - | | | | | | | | | | | |
|---------------|---------|------|-----|-------|----------|---------------|---------|-------------|--------|-------|-----------------------|
| Part | Wattage | | CCT | | Mounting | | Voltage | | Finish | | Accessories |
| HBX | 50 | 50W | 30K | 3000K | [Blank] | Suspended | UNV | 120-277 VAC | WH | White | O Occupancy Sensor |
| | 100 | 100W | 40K | 4000K | SM | Surface Mount | 347 | 347 VAC | | | WG Wire Guard |
| | 150 | 150W | 50K | 5000K | PM | Pendant Mount | WRV | 120-347 VAC | | | SM Surface Mount Kit |
| | 200 | 200W | | | | | | | | | PM Pendant Mount Kit |
| | | | | | | | | | | | C10 10 ft Cabtire Set |
| | | | | | | | | | | | OC-REM PIR Programer |