












Luminance Distribution Chart





Project:	
Location:	
Model#: ARPT403KT2H-UN4-BZ	Type:
Client:	Qty:
Prepared by:	Date:

BUG Graph



Initial Lumen Output: 3887lm

Environmental Rating(s): IP66

Certification Standards: UL Safety US-CA

Efficacy: 108lm/W

UL Classification: Wet Location Listed

CCN Number: IFAM7.E359675

Luminaire Type: Type II-H - Medium

Ambient Operating Temp: -40C to +40C

Limited Product Warranty: 10 Year(s)

Project:	
Location:	
Model#: ARPT403KT2H-UN4-BZ	Type:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

R Tables

R1	73	R9	0
R2	77	R10	46
R3	80	R11	76
R4	76	R12	50
R5	74	R13	73
R6	70	R14	89
R7	80	R15	67
R8	61	--	--

SPD



Source Type: LED

CRI: >70

Chromaticity: x=0.4338 y=0.4030

Manufacturer: Nichia®

L70: 60000 Hrs.

Colour Tolerance: 3 SDCM

Part Number: NVSW219

Colour Temperature: 3000K

ELECTRICAL SPECIFICATIONS

Driver Manufacturer: Inventronics®

Input Frequency: 50/60 hz

Inrush Current: 0.32 A2S

Power Factor at 347Vac: > 0.90

Driver MTBF: 87,000 hrs

Dimming: 1-10Vdc, (10% Min Light Level)

Short Circuit Protection: Auto recovery.

The output shall return to normal when the fault condition is removed.

Driver Part Number: LTC-040S070DSP

Fixture Draw: 35.51W

Max On-Delay: < 1 S

THD at 277Vac(%): < 10%

Max Operating Case Temperature: 90C

Dimming Current mA: 0.2

Driver Certifications: c-RU-us Class 2,

FCC Part 15 Class B, RoHS

Input Voltage: 347Vac

Current Draw at 347Vac: 0.1029

Auxiliary Control: 12 Vdc

THD at 347Vac(%): < 15%

Surge Suppression: 10kV

Over Temperature Protection: Auto recovery. Current returns to normal after over temperature is removed.

PHYSICAL SPECIFICATIONS

Finish Colour: Bronze (RAL-8019)

Mounting: 2.375" O.D. Top Tenon

Lens Type: Clear Optics

Finish Type: Powder Coated

Housing Material: ADC12 Aluminium

Entries: Gasketed Wire Entry

Wiring: Internal Junction

Lens Material: PMMA

Project:	
Location:	
Model#: ARPT403KT2H-UN4-BZ	Type:
Client:	Qty:
Prepared by:	Date:

SHIPPING INFORMATION

OrderingCode(s): ARPT4030KT2H-UN4-BZ


Box Weight: 8.8 kg

Box Quantity: 1

Box Dimensions (L-W-H): 520 x 500 x 220 mm

LINE DRAWING

Line Drawings





Project:	
Location:	
Model#: ARPT403KT2H-UN4-BZ	Type:
Client:	Qty:
Prepared by:	Date:

SERIES ARCHITECTURE

Series Architecture

Part	Wattage	CCT	Mounting	Optics	Voltage	Finish	Accessories
ARPT	40 40W	30K 3000K	Blank 2-3/8" O.D. Tennon	T2 Type II	UNV 120-277VAC	BZ Bronze	O Occupancy Sensor
	80 80W	40K 4000K		T2H Type II with House Side Shield	UN4 347VAC	BK Black	AR-N3PC-UNV 120VAC Photo control
		50K 5000K		T3 Type III		WH White	AR-N3PC-UN4 347VAC Photo control
		AM Amber		T3H Type III with House Side Shield		CC Custom	FSIR-100 Programming remote, sold seperately
				T4 Type IV			
				T4H Type IV with House Side Shield			
				T5 Type V			
				T5H Type V with House Side Shield			

Optional Extras: AR-N3PC-UN4