

Project:						
Location:						
Model#: VPL-WS-3CS	Туре:					
Client:	Qty:					
Prepared by:	Date:					


SERIES SPECIFICATIONS




The Tamlite Lighting VPLWSCS LED Vapour Proof Light Fixture stands out with its robust construction and versatile features, making it an excellent choice for demanding environments. Engineered to perform in wet locations and a range of temperatures, this vapourtight fixture offers adjustable CCT and wattage settings, ensuring optimal illumination and energy efficiency. With its sleek wall mount design and durable die-cast aluminum housing, the Tamlite VPLWSCS is ideal for industrial applications, parking garages, and outdoor areas, providing reliable, customizable lighting solutions.

PERFORMANCE SPECIFICATIONS

Luminance Distribution Chart



Isolux Diagram





Project:	
Location:	
Model#: VPL-WS-3CS	Туре:
Client:	Qty:
Prepared by:	Date:

Zonal Lumen Summary

Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens
0-10	46.84	30-40	366.56	60-70	442.33	90-100	149.76	120-130	54.07	150-160	10.59
10-20	143.47	40-50	466.28	70-80	328.31	100-110	104.16	130-140	36.92	160-170	4
20-30	250.07	50-60	502.67	80-90	222.53	110-120	74.84	140-150	21.82	170-180	0.87

Total Initial Lumen Output; 3226,09 Im at; 40W, 4000K

Co-efficient of Utilization

Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

RC		8	0			7	70			50			30			10		0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	116	116	116	116	111	111	111	111	103	103	103	96	96	96	89	89	89	86
1	102	96	91	86	98	92	87	83	85	81	78	79	76	73	73	71	68	65
2	91	81	73	67	87	78	71	65	72	66	61	67	62	57	62	58	54	51
3	82	70	61	53	78	67	59	52	62	55	49	57	51	46	53	48	44	41
4	74	61	51	44	71	59	49	42	54	46	40	50	44	38	46	41	36	33
5	68	54	44	36	65	52	42	35	48	40	34	44	37	32	41	35	30	28
6	62	48	38	31	59	46	37	30	43	35	29	39	33	27	37	31	26	23
7	57	43	33	27	55	41	32	26	38	30	25	36	29	24	33	27	23	20
8	53	39	29	23	50	37	29	23	35	27	22	32	26	21	30	24	20	18
9	49	35	26	20	47	34	26	20	32	24	19	29	23	18	27	22	17	15
10	46	32	24	18	44	31	23	18	29	22	17	27	21	16	25	20	16	14

Initial Lumen Output: 3300lm
UL Classification: cULus

Efficacy: 110lm/w
Ambient Operating Temp: -40C to +45C

Environmental Rating(s): IP65
Limited Product Warranty: 5 YEARS

LED SPECIFICATIONS

Source Type: LED **CRI:** >80 **L90:** >50,000hrs



Project:					
Location:					
Model#: VPL-WS-3CS	Туре:				
Client:	Qty:				
Prepared by:	Date:				

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac Input Frequency: 50/60HZ Fixture Draw: 30W

Current Draw at 120Vac: 0.333A Max On-Delay: THD at 120Vac(%): 9.67 Power Factor at 120Vac: 0.99

Power Factor at 277Vac: 0.91 THD at 277Vac(%): 14.78

PHYSICAL SPECIFICATIONS

Max Operating Case Temperature: 45C

Finish Colour: GREY Finish Type: Powder Coated Mounting:: Surface
Housing Material: Die-cast Aluminium Lens Material: Polycarbonate Weight: 2.43lbs

Entries: one back, four sides

SHIPPING INFORMATION

OrderingCode(s): VPL-WS-3CSBox Quantity: 1Box Dimensions (L-W-H):Box Weight: 1.2KGCarton Quantity: 6315*120*120mm

Carton Weight: 7.8kg Carton Dimensions (I-W-H):

375*325*355mm