


Project:	
Location:	
Model#: TAVL24-3SN	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS





PERFORMANCE SPECIFICATIONS

Zonal Lumen Summary

Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens	Zone	Lumens
0-10	28.5	30-40	160.54	60-70	169.54	90-100	0	120-130	0	150-160	0
10-20	82.33	40-50	177.95	70-80	150.46	100-110	0	130-140	0	160-170	0
20-30	127.45	50-60	180.39	80-90	124.72	110-120	0	140-150	0	170-180	0

Total Initial Lumen Output; 1201.88 lm

Initial Lumen Output: 1,250 lm Luminaire Type: Surface Direct Indirect Ambient Operating Temp: -18°C ~ 40°C /

0°F ~ +104°F

Efficacy: 72 lm/W Max Candela: 302 cd (90H,5V)
Environmental Rating(s): IP20 UL Classification: Damp Location


Environmental Rating(s): IP20 UL Classification: Damp Location Listed
Certification Standards: cETLus Limited Product Warranty: 1 Year



Project:		
Location:		
Model#: TAVL24-3SN	Туре:	
Client:	Qty:	
Prepared by:	Date:	

LED SPECIFICATIONS

SPD



Source Type: LED **CRI:** 90 **L70:** >54,000 Hrs

Colour Temperature: 3000K Colour Tolerance: +/- 300K

ELECTRICAL SPECIFICATIONS

Input Frequency: 50/60hz Fixture Draw: 17W Input Voltage: 120-277Vac

Current Draw at 120Vac: 0.1417A Max On-Delay: < 1s Power Factor at 120Vac: 90.00%

PHYSICAL SPECIFICATIONS

Housing Material: Steel Lens Material: Opal Acrylic Lens Type: Diffuse

Entries: Box Mount

SHIPPING INFORMATION

OrderingCode(s): TAVL24-3SN (0425-1489)

Box Weight: 0.82 Kg / 1.8 lbs **Box Quantity: 1 Box Dimensions (L-W-H):** 24.75 x 4.75 x

3.25Inches / 628.65 x 628.65 x 82.55mm



Project:	
Location:	
Model#: TAVL24-3SN	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES ARCHITECTURE

Series Architecture

Example: TAVL24-3SN

Series	Length	Colour Temp	Finish		
TAVL	[24]:24"	[-3]:3000K	[SN] : SATIN NICKEL		
		[-4]:4000K			