

Project:	
Location:	
Model#: RMC3GWRC	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



The RMC3GWRC Is a thermoplastic running man LED exit combo which offers a modern look with remote capability as well as long lamp life, energy efficiency, and uniform illumination; all components feature a snap-fit construction for speed and ease of installation. Field installed heads and mounting canopy are included within the fixture. The unit also comes with a LED indicator for charge rate, "ON" and a push to test switch



PERFORMANCE SPECIFICATIONS

Initial Lumen Output: 2 X 150 lm
Environmental Rating(s): Damp location
Limited Product Warranty: 2 years for battery 3 years for fixture

Beam Angle: 28.5°
Ambient Operating Temp: 10°C to 40°C / 50°F to +104°F

Luminaire Type: Combo
Certification Standards: UL924, C22.2 No. 141-15

LED SPECIFICATIONS

Source Type: LED
Colour Temperature: 6000K

CRI: > 80

L70: >54,000 Hrs

ELECTRICAL SPECIFICATIONS

Input Voltage: 120/347Vac
Current Draw at 347Vac: 24mA
Power Factor at 120Vac: > 0.7
Max Operating Case Temperature: 40

Input Frequency: 50/60 Hz
Inrush Current: 1A
Power Factor at 277Vac: > 0.7
Surge Suppression: YES

Current Draw at 120Vac: 60mA
Max On-Delay: 1S
Power Factor at 347Vac: > 0.7
Short Circuit Protection: YES

EMERGENCY INFORMATION

Input Voltage: 120/347V
Emergency Runtime: >90minutes
Emergency Certifications: UL924

Max Power Input: 7.2W
Battery Type: Ni-MH

Standby Power: 3W
Battery Recharge Time: 24hours

PHYSICAL SPECIFICATIONS

Finish Colour: White
Lens Material: Polycarbonate

Mounting: Back, Top or side mount.
Canopy included
Weight: 1.82 kg

Housing Material: ABS

SHIPPING INFORMATION

OrderingCode(s): 0627-8574
RMC3GWRC LED RM PLASTIC COMBO 2
HEAD RC 120/347V
Carton Quantity: 6

Box Quantity: 1
Carton Dimensions (L-W-H): 410 x 370 x
255 mm / 0.3 x 0 x 410 inches

Box Dimensions (L-W-H): 356 x 254 x 76
mm / 14 x 10 x 3 inches
Carton Weight: 012.3 Kg

LINE DRAWING

Line Drawings

