

Project:	
Location:	
Model#: SEL-2	Туре:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS



The Tamlite SEL-2 Emergency Light delivers high performance and reliability with steel housing, dual adjustable LED heads, and 32W remote capability. Its compact, easy-install design and strong battery backup ensure safety during outages. Suitable for commercial, industrial, and residential use, it provides dependable illumination and visibility. Includes 120Vac 10A field-installed plug cord.










PERFORMANCE SPECIFICATIONS

Isolux Diagram



Initial Lumen Output: 212 lm

Beam Angle: 600

Ambient Operating Temp: 3°C to 30°C /

37.4°F to +86°F

Efficacy: 35

Luminaire Type: Emergency Battery

Certification Standards: UL924, C22.2

No. 141-15

Max Candela: 170.9cd

Environmental Rating(s): Damp location Limited Product Warranty: 2 years for

battery 3 years for fixture



Project:	
Location:	
Model#: SEL-2	Туре:
Client:	Qty:
Prepared by:	Date:

LED SPECIFICATIONS

Source Type: LED **CRI:** > 80 **L70:** >54,000 Hrs

Colour Temperature: 6000K

ELECTRICAL SPECIFICATIONS

Input Voltage: 120V-347Vac Input Frequency: 50/60 Hz Current Draw at 120Vac: 0.19A

Over Temperature Protection: YES Short Circuit Protection: YES

EMERGENCY INFORMATION

Emergency Runtime: >90minutes Battery Type: lead battery Battery Recharge Time: 24hours

Emergency Certifications: UL924

PHYSICAL SPECIFICATIONS

Finish Colour: White Mounting: Back Wall Mount Lens Material: PC

SHIPPING INFORMATION

OrderingCode(s): 0625-2654 SEL-2 LED Box Quantity: 1 Box Dimensions (L-W-H): 330 x 254 x

STEEL EM 32W RC 120/347 Carton Dimensions (I-W-H): $470 \times 340 \times 10^{-2}$

Carton Quantity: 5 255 mm / 0.3 x 0 x 470 inches Carton Weight: 013.6 Kg

102 mm / 13 x 10 x 4 inches